

LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SE 1/4 Section Number 12 Township Number T 6 S Range Number R 5 E
 County: Piley
 Distance and direction from nearest town or city street address of well if located within city?
Take 77 South Watermillers to Col. line then 3 West and 1 7/10 Southwest Side
 WATER WELL OWNER: Marion Brenner
 RR#, St. Address, Box # :
 City, State, ZIP Code: Randolph, KS 66554 Board of Agriculture, Division of Water Resources
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 2740.41 ft.
 Depth(s) Groundwater Encountered: 1.2 ft. 4.1 ft. 4.1 ft.
 WELL'S STATIC WATER LEVEL: 2740.41 ft. below land surface measured on mo/day Aug. 4 - 1984
 Pump test data: Well water was 30 gpm: Well water was 10 ft. after 18 hours pumping 6" gpm
 Est. Yield 30 gpm: Well water was 10 ft. after 18 hours pumping 6" gpm
 Bore Hole Diameter: 10 in. to 18 ft., and 6" in. to 60 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 11 Injection well
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

TYPE OF BLANK CASING USED:
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile ☐ 9 Other (specify below)
☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 7 Fiberglass ☐ 10 Asbestos-cement
 Blank casing diameter: 7.0 in. to 5" ft. Dia to bottom 40 on lower end Ripped ft.
 Casing height above land surface: 12.5 in., weight 2.60 lbs./ft. Wall thickness or gauge No. 2.60 Wall
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 8 RMP (SR) ☐ 11 Other (specify)
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☐ 3 Mill slot ☐ 5 Gauzed wrapped ☒ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 60 ft. to 20 ft. From 60 ft. to 20 ft.
 GRAVEL PACK INTERVALS: From 60 ft. to 0.18 ft. From 60 ft. to 0.18 ft.

GROUT MATERIAL: ☒ 1 Neat cement ☐ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout intervals: From 6 ft. to 18 ft. From 6 ft. to 18 ft.
 What is the nearest source of possible contamination:
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage ☐ 14 Hog Pens
 Direction from well? South How many feet? 660

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
6	2	top Soil			
2	18	clay, Red			
18	21	clay, yellow			
21	41	Rock, Limestone & Water all thru it			
41	60	Chale, Blue			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Aug. 4 - 1984 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 237 This Water Well Record was completed on (mo/day/year) Aug. 4 - 84
 under the business name of Strader Drilling Co by (signature) Harold Strader
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.