

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Riley, Fraction: SW 1/4 NW 1/4 SW 1/4, Section Number: 13, Township Number: T 60, Range Number: R 60

Distance and direction from nearest town or city street address of well if located within city? From Randolph 60 North 7 miles on 77 Hwy to Seward Creek then go East 2 miles to N. Hs. Riviere then go Apex 3/4 South

2 WATER WELL OWNER: Clifford W. Sparks, RR#, St. Address, Box #: 3409 Trees Mill Circle, City, State, ZIP Code: Manhattan, KS 66503

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Diagram showing a 3x3 grid with 'X' in the SW quadrant]
4 DEPTH OF COMPLETED WELL: 80 ft.
Depth(s) Groundwater Encountered (1)... 37 ft. (2)... ft. (3)... ft.
WELL'S STATIC WATER LEVEL: 30 ft. below land surface measured on mo/day/yr.
Pump test data: Well water was... ft. after... hours pumping... gpm
Est. Yield: 1.5 gpm: Well water was... ft. after... hours pumping... gpm
WELL WATER TO BE USED AS: 1 Domestic, 2 Irrigation, 3 Feedlot, 4 Industrial, 6 Oil field water supply, 7 Domestic (lawn & garden), 8 Air conditioning, 9 Dewatering, 10 Monitoring well, 11 Injection well, 12 Other (Specify below)
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr
Sample was submitted... Water well disinfected? Yes No

5 TYPE OF CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought Iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below)
Casing joints: Glued, Clamped, Welded, Threaded
Blank casing diameter: 5 in. to 60 ft., Diameter
Casing height above land surface: 2 in., Weight 40 lbs./ft., Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RM (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Wire wrapped, 6 Torched wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft.
GRAVEL PACK INTERVALS: From 32 ft. to 80 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other
Grout Intervals: From 5 ft. to 32 ft., From 32 ft. to ft., From ft. to ft.
What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/gas well, 16 Other (specify below)
Direction from well? None Close
How many feet? ft.

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-1 Top Soil, 1-32 Brown Clay, 32-38 Limestone (Water), 38-45 Yellow Shale, 45-52 Limestone, 52-64 Gray Shale, 64-75 Gray Oily Shale, 75-80 Limestone.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 8/30/2010. This record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451. This Water Well Record was completed on (mo/day/year) 9/15/2010 under the business name of Waldeman Well Drilling by (signature) Craig A. Waldeman

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.