## KOLAR Document ID: 1622579

	WELL R			WWC-5		vision of Wat						
		Correction		ge in Well Use	1	ources App. 1	-		Well ID			
1 LOCATION OF WATER WELL:     Fraction					ction Numb	1 0						
$\begin{array}{c c} County: & 1/4 & 1/4 \\ \hline & 1/4 & 1/4 \\$												
						treet or Rural Address where well is located (if unknown, distance and						
Address:							irection from nearest town or intersection): If at owner's address, check here:					
Address:												
City:			State:	ZIP:								
3 LOCAT	E WELL				C.							
4 DEPTH OF COMPLETED WELL:												
SECTIC	SECTION BOX: Depth(s) Groundwater Encountered: 1)											
1	2) ft. 3) ft., or 4)					Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude:						
				n. yr)					`			
NW	NE			yr)		☐ GPS (unit make/model:) (WAAS enabled? ☐ Yes ☐ No)						
	NE	Pump test d				Land Survey Topographic Map						
w	E	after hours pumping gpm						Mapper:				
CW	SE	Well water was ft.										
Sw	SE		after hours pumping gpm				6 Flowering ft Crowned Level TOC					
		Estimated Y			6 Elevation:ft.  Ground Level  TOC							
	S	Bore Hole I			Source: Land Survey GPS Topographic Mag							
	nile	DE LIGED		in. to	п.			Other	•••••	,		
7 WELL WATER TO BE USED AS:												
1. Domestic:       5. □ Public Water Supply: well ID         □ Household       6. □ Dewatering: how many wells?												
	□ Lawn & Garden											
	Livestock I Livestock I Livestock											
	2. □ Irrigation 9. Environmental Remediation: well ID .						<ul><li>12. Geothermal: how many bores?</li><li>a) Closed Loop □ Horizontal □ Vertical</li></ul>					
3. $\Box$ Feedlo								Loop  Surface Di				
	4. Industrial Recovery Injection						13. $\Box$ Other (specify):					
Was a chemical/bacteriological sample submitted to KDHE?  Yes  No If yes, date sample was submitted:												
Water well disinfected? Ves No												
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded												
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.												
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No												
TYPE OF SCREEN OR PERFORATION MATERIAL:												
$\Box \text{ Steel} \qquad \Box \text{ Stainless Steel} \qquad \Box \text{ PVC} \qquad \Box \text{ Other (Specify)} \dots$												
□ Brass □ Galvanized Steel □ None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:												
Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)												
Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)												
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.												
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft. to ft.												
9 GROUT MATERIAL:  Neat cement Cement grout Bentonite Other												
Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft. to												
	rce of possibl			potential source of cont				<b>—</b> • •				
			Lateral Line			Livestock P			cide Storage			
Sewer			Cess Pool	Sewage Lag		Fuel Storage			oned Water			
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well												
Other (Specify) Direction from well? ft.												
10 FROM	TO		ITHOLO		FROM	ТО		HO. LOG (cont.) or		GINTERVALS		
	<u> </u>											
	<u> </u>											
	<u> </u>				Notes:	1	1					
11 CONT	11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged											
under my j	urisdiction ar	nd was compl	leted on (n	no-day-year)	and	this record	is tru	e to the best of m	y knowled	ge and belief.		
Kansas Wa	ter Well Con	tractor's Lice	ense No	This Wa	ter Well Red	cord was co	mple	ted on (mo-day-ye	ear)			
under the b	usiness name	<u>e of</u>				·····		<u></u>				
KS Donort				ELL OWNER and retain o						785-206 3565		
KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565. Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212												