			WATER	WELL RECORD	Form WWC-5	KSA 8	2a-1212			
—			Fraction	3773	_	tion Number	1 - '		Range Number	
				NE ¼ N		4	т /	S	R 13E E/W	
Distance and direction from nearest town or city street address of well if located within city? 4 miles south of Soldier										
2 WATER WELL OWNER: Dean Wheeler										
RR#, St. A			88th Rd.			Board of Agriculture, Division of Water Resources				
City, State,	ZIP Code	Soldier	, KS 66	540	Application Number:					
3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL. 100. ft. ELEVATION:										
Depth(s) Groundwater Encountered 1										
WELL'S STATIC WATER LEVEL 65 ft. below land surface measured on mo/day/yr 2/27./98. Pump test data: Well water was ft. after hours pumping										
	Est. Yield 8 gpm: Well water was ft. after hours pumping Bore Hole Diameter . 8 . 3/4 .in. to ft., and in. to									
Mile W							8 Air conditioning			
-	i		1 Domestic							
	- SW	SFI							Other (Specify below)	
	!		_		-	•			, mo/day/yr sample was sub-	
li –		mitt		zotoriologicar sample	Submitted to be		Vater Well Disinfected			
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . X Clamped										
_	1 Steel 3 RMP (SR)			6 Asbestos-Cement 9 Other (specify below)					ded	
	2 PVC 4 ABS			7 Fiberglass				Thre	aded	
Blank casing diameter										
Casing height above land surface24"in., weight2.82										
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement										
1 Steel 3 Stainless steel				5 Fiberglass	s 8 RMP (SR) 11 Other (specify))	
2 Bra	iss	4 Galvanized s	teel	6 Concrete tile	9 ABS 12 None used (open hole)				pen hole)	
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)										
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes										
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From										
From										
GRAVEL PACK INTERVALS: From										
From ft. to ft., From ft. to ft.										
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other										
Grout Intervals: From4ft. to24ft., Fromft. toft., Fromft.										
							Abandoned water well			
1 Septic tank 4 Lateral lines							el storage		Dil well/Gas well	
2 Sewer lines 5 Cess pool							rtilizer storage	16 (Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage										
Direction fr FROM	TO TO	West	ITHOLOGIC L	OG	FROM	TO How r	nany feet? 300	IGGING	INTERVALS	
0	2	Top Soil	THOLOGIC L		40	45	Shaley LS-G		MILITALO	
2	7	Clay-Brown			45	47	Shale-Grey			
7	9	Clay-Tan			47	49	Limestone-T			
9	13	Limestone-	l'an		49	53	Shale-Tan-G			
13	17	Limestone-			53	_55		-		
17	18		lle-grey Hard			61	Shale-Light Grey			
18	19	Shale-Black				64	Shale-Red			
19	20		ale-Grey			67	Shale-Tan			
20	24	_	e-Black			71	Limestone-Tan			
24	25		e-Dark Grey			73	Shale-Tan			
25	26		one-Grey			75	Limestone-Yellow			
26	30		rey			77	Shale-Grey			
30	33	Shale-Tan	-Tan				Shale-Black/Dark Grey Limestone-Grey			
33	35	Limestone-			77 83	83 85		rey	1	
35	40	Shale-Grey			85	100	Shale-Grey			
7 CONTR	RACTOR'S	OR LANDOWNER'S	CERTIFICATIO	ON: This water well w	was (1) constru	cted, (2) re	econstructed, or (3) pl	ugged un	der my jurisdiction and was	
completed on (mo/day/year)02/27/98										
Water Well Contractor's License No. 182 This Water Well Record was completed on (modfwller) 3-26-99										

under the business name of STRADER DRILLING CO., INC.