

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Jackson	NW 1/4 NW 1/4 SW 1/4	2	T 7 S	R 14E E/W

Distance and direction from nearest town or city street address of well if located within city?
4 miles west and 1/2 mile north of holton

2 WATER WELL OWNER: **Paul Longren**
 RR#, St. Address, Box # : **23380 L Rd**
 City, State, ZIP Code : **Holton, Ks 66436**
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 10.0 ft. ELEVATION:		
	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.		
	WELL'S STATIC WATER LEVEL 6.3 ft. below land surface measured on mo/day/yr 6--1.6--0.5		
	Pump test data: Well water was ft. after hours pumping gpm		
	Est. Yield 7 gpm: Well water was ft. after hours pumping gpm		
WELL WATER TO BE USED AS:		5 Public water supply	8 Air conditioning
		1 Domestic	3 Feedlot
		6 Oil field water supply	9 Dewatering
		2 Irrigation	4 Industrial
		7 Domestic (lawn & garden)	10 Monitoring well
		11 Injection well	12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No**X**...; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes **X** No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
			Threaded
Blank casing diameter 5 in. to ft., Dia in. to ft.			
Casing height above land surface 24 in., weight 2.82 lbs./ft. Wall thickness or guage No.258			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-Cement
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS
			11 Other (Specify)
			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
			11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 76 ft. to 96 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 24 ft. to 100 ft., From ft. to ft.			

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 **Bentonite** 4 Other

Grout Intervals: From**0**..... ft. to**24**..... ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	ditch

Direction from well? **west** How many feet? **75'**

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	9	clay brown			
9	31	clay yellow brown			
31	35	clay brown grey streaks			
35	37	clay grey			
57	59	boulders red			
59	77	clay grey			
77	81	fine/course sand chert grey			
81	92 94	shale grey			
94	96	shale blue grey			
96	100	shale grey limy			
100		limestone grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)**7--28--05**..... and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No**182**..... This Water Well Record was completed on (mo/day/yr)**7-28-05**..... under the business name of **Strader Drilling Co., Inc.** by (signature) *Jim Strader*