

1 LOCATION OF WATER WELL: County: JACKSON Fraction NW 1/4 NW 1/4 SE 1/4 Section Number 16 Township Number T 7 S Range Number R 15 EW

Distance and direction from nearest town or city street address of well if located within city?
 1 1/2 south of Holton

2 WATER WELL OWNER: National Marketing (Coach House)
 RR#, St. Address, Box #: c/o Harvey Sides Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: 1726 N. Topeka Topeka, KS 66608 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the center section]

4 DEPTH OF COMPLETED WELL: 81 ft. ELEVATION: [Blank]
 Depth(s) Groundwater Encountered 1. [Blank] ft. 2. [Blank] ft. 3. [Blank] ft.
 WELL'S STATIC WATER LEVEL: 46' ft. below land surface measured on mo/day/yr 5-21-90
 Pump test data: Well water was [Blank] ft. after [Blank] hours pumping [Blank] gpm
 Est. Yield: 60 gpm; Well water was [Blank] ft. after [Blank] hours pumping [Blank] gpm
 Bore Hole Diameter: 12" in. to [Blank] ft., and [Blank] in. to [Blank] ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
~~XXXXXX~~ 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No [Blank]; If yes, mo/day/yr sample was submitted 5-30-90
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5" in. to 0-70 ft., Dia 5" in. to 80-81 ft., Dia [Blank] in. to [Blank] ft.
 Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft., From [Blank] ft. to [Blank] ft.
 GRAVEL PACK INTERVALS: From 30 ft. to 81 ft., From [Blank] ft. to [Blank] ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 30 ft., From [Blank] ft. to [Blank] ft., From [Blank] ft. to [Blank] ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? north How many feet? 200'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	46	Clay-Brown			
46	59	Clay-Blue			
59	63	Fine Sand-Brown			
63	79	Fine Sand-Coarse Sand-Med-Pea Gravel-Brown			
79	81	Limestone-Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-21-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 6-18-90 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Skrey