* 180	Her		WATE	R WELL RECORD	Form W/M	/C-5 KSA 82	a_1212				
		TER WELL:	Fraction	WELL RECORD	Krolli W	Section Number		hip Number	Rai	nge Number	
County: L	_eaven	Uorth	Sw 1/4	5w 1/4 5	W 1/4	26	Т	7 (5)	R	20 BW	
Distance a	and direction	from nearest town	or city street a	ddress of well if loos	ted within ci	ty? 2.55.	IW OF	POTTER			
			<u> </u>				•				
2 WATE	R WELL OW	NER: Jim &	Brown								
RR#, St. /	Address, Bo	×# : Box 83					Boar	d of Agriculture, I	Division o	f Water Resources	
City, State	, ZIP Code	EASTO	V. KAn	SAS 660	120			ication Number:			
3 LOCATI	E WELL'S L	OCATION WITH 4	DEPTH OF C	OMPLETED WELL.	51	ft. ELEV	ATION:	1078 RM	÷	,	
_ AN "X"	IN SECTION	N BOX:	epth(s) Ground	water Encountered	1	<i>.⊋.7</i> ft.	2	ft. 3			
ī	!	ı W	ELL'S STATIC	WATER LEVEL	<i>3</i>	ft. below land su	urface measur	ed on mo/day/yr	11-1	8-81	
Pump test data: Well water was ft. after hours pumping gpm											
T	Est. Yield 20 gpm: Well water was ft. after hours pumping gpm										
. w L	i	l Bo	ore Hole Diame	eter <b>. / 0</b> in. <sup>.</sup>	to <i>5.6</i> .		and	in	to		
掌∾┝		i w	ELL WATER T	O BE USED AS:	5 Public	water supply	8 Air condit	ioning 11	Injection	well	
ī	sw		1 Domestic	3 Feedlot	6 Oil field	water supply	9 Dewaterir	ng 12	Other (Sp	ecify below)	
		;	2 Irrigation	4 Industrial		nd garden only					
1 [	Was a chemical/bacteriological sample submitted to Department? Yes; If yes, mo/day/yr sample was si								r sample was sub-		
<u> </u>		s mi	tted			w		nfected? Yes		No	
5 TYPE	OF BLANK (	CASING USED:		5 Wrought iron	8 Cd	oncrete tile	CASIN	G JOINTS: Glue	بسبة . ا	Clamped	
1 St	eel	3 RMP (SR)		6 Asbestos-Cemer	nt 9 Ot	her (specify belo	ow)				
2 P\	<u>/C</u>	4 ABS		7 Fiberglass							
Blank casing diameter											
Casing height above land surface											
		R PERFORATION N				PVC		Asbestos-ceme			
1 St		3 Stainless st		5 Fiberglass		RMP (SR)					
2 Br		4 Galvanized		6 Concrete tile		ABS		2 None used (op	•		
		RATION OPENINGS		5 Gauzed wrapped			8 Saw cu	•	11 None	e (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
2 Louvered shutter       4 Key punched       7 Torch cut       10 Other (specify)         SCREEN-PERFORATED INTERVALS:       From       21       ft. to       34       ft., From       ft. to       ft. to											
From											
	SDAVEL DA	CK INTERVALS:		.1. <b>4</b> ft. to							
`	OI IAVEL FA	OK INTERVALS.	From	ft. to		ft., Fr				i i	
From ft. to ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite. 4 Other											
Grout Intervals: From											
		ource of possible co					stock pens			l water well	
1 Septic tank 4 Lateral lines			ines				11 Fuel storage 15 Oil well/Gas well				
2 Sewer lines 5 Cess poo			ool	8 Sewage lagoon			12 Fertilizer storage 16 Other (specify below)				
3 W	atertight sew	ver lines 6 Seepage		9 Feedyard			13 Insecticide storage				
	from well?	_		·		How m	any feet? 15	0			
FROM	ТО		LITHOLOGIC	LOG	FRO	и то		LITHOLOG	IC LOG	- 1	
0	3	TOP SOIL									
3	26	Chy brown	,								
26	28	Cherty Lim	estone,9	rey loose							
28	32	Shale, gray									
<u>52</u>	57	LIMESTONE	grey_								
7 00:	DAOTOC:O	DD   ANDONE :====	OFFIT :	O				. (0)			
1 CONTI	HAUTUR'S (	OR LANDOWNER'S /year)// /.8	CERTIFICATI C- PI								
			182					the best of my kn		and belief. Kansas	
		,									
INSTRUC	TIONS: Use	typewriter or ball poi	nt pen. Pl FAS	E PRESS FIRMI Y	and PRINT	by (sign learly. Please fill	in blanks und	derline or circle the	e correct :	answers. Send ton	
under the business name of STrader Dala Co. The by (signature) Solution or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL											
OWNER 8	and retain or	ne for your records.									

PCF