

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well: County CLAY		Fraction NW 1/4 SW 1/4 SE 1/4		Section number 35		Township number T 7 S R 3 EAW		Range number	
2. Distance and direction from nearest town or city: 1W-1N Street address of well location if in city: CLAY CENTER				3. Owner of well: CLARENCE SMITH R.R. or street: Box 208 City, state, zip code: BELLEVILLE KANSAS 66935					
4. Locate with "X" in section below: Sketch map:				6. Bore hole dia. 30 in. Completion date 4/25 Well depth 68 ft. 6/26/75					
				7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary					
				8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other					
5. Type and color of material				From		To		9. Casing: Material AC Height Above or below	
Top soil + clay				0		28		Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in.	
gravel				28		33		RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 24 lbs./ft.	
FINE GRAVEL				33		44		Dia. 1 1/2 in. to 68 ft. depth Wall Thickness: inches 3/4	
GOOD GRAVEL				44		54		Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 34	
CLAY				54		57		10. Screen: Manufacturer's name JOHNSON	
FINE GRAVEL				57		64		CONCRETE	
GOOD GRAVEL				64		71		Type ASBESTOS CEMENT dia. 16 ID	
CREEK GRAVEL				71		74		Slot/gauge 1/8" Length 26 FT	
STOP ON SHALE				74				Set between 42 ft. and 68 ft.	
								Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/8-1/4	
								11. Static water level: mo./day/yr. 26 ft. below land surface Date	
								12. Pumping level below land surfaces: 45 ft. after 1/2 hrs. pumping 1200 g.p.m.	
								ft. after _____ hrs. pumping _____ g.p.m.	
								Estimated maximum yield _____ g.p.m.	
								13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date 6/26/75	
								14. Well head completion: 12 inches above grade	
								15. Well grouted? <input checked="" type="checkbox"/> YES	
								With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete	
								Depth: From 0 ft. to 10 ft.	
								16. Nearest source of possible contamination: NONE	
								ft. _____ Direction _____ Type _____	
								Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
								17. Pump: <input type="checkbox"/> Not installed	
								Manufacturer's name JACUZZI BEOS	
								Model number LCR HP 30 Volts 230	
								Length of drop pipe 60 ft. capacity 1200 g.p.m.	
								Type:	
								<input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine	
								<input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating	
								<input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
(Use a second sheet if needed)									
18. Elevation:		19. Remarks:							
Topography:		20. Water well contractor's certification:							
<input type="checkbox"/> Hill		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.							
<input type="checkbox"/> Slope		GEO COX + SONS, INC 258							
<input type="checkbox"/> Upland		Business name _____ License No. _____							
<input checked="" type="checkbox"/> Valley		Address CLIFTON KANSAS							
		Signed Francis Cox Date 11-26							
		Authorized representative							

T-7
 R-30
 W-35
 Sec 1/4 NW SW SE
 1/4 1/4 1/4