CORRECTION TO WATER WELL RECORD (WWC-5)

The following correction(s) was made to the attached WWC-5 log, in order to file the item or to rectify lacking or incorrect information.

Fraction (1/4 1/4) Section-Township-Range changed:
listed as SE NW NW, 1 - 6-75 - 4-5 E
changed to SE NW NW, 1-75-4E
Other changes: Initial statements:
Changed to:
Comments:
verification method: Written & legal description, position on plat map, and Lasita 1:24,000 topo. map. initials: Offst date: 6/16/2000

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment Bureau of Water Industrial Programs, Bldg 283, Forbes Field, KS 66620

			WATE	R WELL RECORD	Form WM		KSA 82a-				
_		ER WELL:	Fraction			_	Number	Township Nun		Range Number	
County: R		from poarcet to:			NW 1/4	<u>1</u>		т 6-7	S	R 4-5 (B)W	
Distance and direction from nearest town or city street address of well if located within city? 1 North, 3 East & 21 North of Green											
					11						
2 WATER WELL OWNER: Wendell Eggerman RR#, St. Address, Box # : 17833 Lasita Rd. Board of Agriculture, Division of Water Resource:											
			, KS. 67		Application Number:						
3 LOCATE WELL'S LOCATION WITH A DEPTH OF COMPLETED WELL 140 # ELEVATION:											
AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1											
WELL'S STATIC WATER LEVEL . 1.1.5 ft. below land surface measured on mo/day/yr5/1.5./.00											
* Pump test data: Well water was ft. after hours pumping											
	Est. Yield 1.0-1.5 gpm: Well water was ft. after hours pumping									mping gpm	
ا ب ا	Bore Hole Diameter . 9 in. to										
** w	!	!] .	WELL WATER	TO BE USED AS:	5 Public			8 Air conditioning			
ī L	_ sw	SE	1 Domestic		6 Oil field	water s	supply	9 Dewatering	1 <u>2 (</u>	Other (Specify below)	
	ï	ī	2 Irrigation	4 Industrial						stock	
Į L								epartment? Yes			
cl Type o	S DI 4416 C	ASING USED:	mitted	E Marianta inca	0.00					No Ⅰ* Clamped	
1 Ste		ASING USED: 3 RMP (SI	D)	5 Wrought iron 6 Asbestos-Ceme			tile ecify below			ed	
2 PV		4 ABS	n)	7 Fiberglass		٠.	-			ded	
			in to 120								
Blank casing diameter 5 in. to 120 ft., Dia in. to ft. Casing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No • 214											
		R PERFORATIO		, .		PVC		10 Asbes			
1 Ste	el	3 Stainless	s steel	5 Fiberglass	8				Other (specify)		
2 Bra	ass	4 Galvaniz	ed steel	6 Concrete tile	9	ABS		12 None	used (ope	en hole)	
SCREEN (OR PERFOR	RATION OPENIN	IGS ARE: 5 Gauze		auzed wrappe	wrapped 8 Sa		8 Saw cut		11 None (open hole)	
1 Co	1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes										
	uvered shutt		ey punched		orch cut						
SCREEN-PERFORATED INTERVALS: From. 120 ft. to 140 ft., From ft. to ft.											
From. ft. to											
G	MAVEL PA	CK INTERVALS:	From	ft. t			ft., Fron			j	
6 GBOUT	MATERIAL	1 Neat				entonite			11. 11	<u>, </u>	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other											
		ource of possible					10 Livest			pandoned water well	
1 Se	ptic tank	4 Later	al lines	7 Pit privy			11 Fuels	•	15 Oil well/Gas well		
2 Se	wer lines	5 Cess	pool	8 Sewage	lagoon	12 Fertilizer storage		zer storage	16 Other (specify below)		
3 Wa	atertight sew	er lines 6 Seep	age pit	9 Feedyard	d		13 Insect	ticide storage			
Direction for		West					How man				
FROM	TO	m1	LITHOLOGIC	LOG	FROI	v	то	PLU	GGING II	NTERVALS	
0	8	Topsoil Limesto	20								
		Tan Sha									
8 15	15 18	Gray Sh									
18	24	Limesto								· · · · · · · · · · · · · · · · · · ·	
24	47	Red Sha									
47	56	Limesto									
56	61	Yellow									
61	63	Gray Shale									
63	77	Yellow	Shale								
77	108	Red Sha									
108	132		ne Layers	5				·			
132	142	Gray Sh	ale								
						-			· · · · · · · · · · · · · · · · · · ·		
1						L_	L				
										er my jurisdiction and was	
									of my kno 5/30/	owledge and belief. Kansas	
				This Wate	er well Hecord					.¥ M	
under the business name of Blue Valley Drilling by (signature)											