WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | Section | number | Township number | Range number | | 1 |
|---|-------------------|-----------------------|---------|--------|---|--|---------------|--------------|
| 1. Location of well: | RILEY | NE VANE VASH | 1/4 2 | | | R 6 6 | (a) | • |
| 2. Distance and direction from nearest town or city: Street address of well location if in city: In ite South of Randolph R.R. or street: Randolph Ko. | | | | | | | | |
| 2. Distance and direction from nearest town or city: Street address of well location if in city: Mike South of Randolph R.R. or street: Randolph Ko. City, state, zip code: | | | | | | | | |
| 4. Locate with "X" i | in section below: | Sketch map: | | | 6. Bore hole dia. 65 in Well depth 45 ft. | . Completion date 2/10/ | 25 | |
| NW | i NE | | | | 7. 🗶 Cable tool Rotary | | otary | |
| W W W | NE ! ! | | | | 8. Use: 🗶 Domestic 🔔 Po | | _ | |
| SW | SE | | | | | il field water Other | - | 1 |
| | | | | | Threoded Welded RMP PVC \$4.40 | 2_Weight <u> </u> | _in. /ft. | |
| 5. Type and color of | | | From | То | Dia. <u>6</u> "in. to 115 ft. dep Dia. <u>in.</u> to <u>ft. dep</u> | oth Wall Thickness: inches of the gage No. 14" | or | |
| 3. 1/pc and color of | | | | | 10. Screen: Manufacturer's | name | _ | |
| (00) | Soil | - | O | 10 | Type DUC Sh 40 | Dia. 5" | _ | |
| yellow | Rock | | 10 | 14 | Slot/gauze S/nted Set between | Length | ft. | |
| Wellow | Clau | | 14 | 24 | Gravel pack? ft. c | | _ft. | • |
| Gellow | Rock | | 24 | 30 | 11. Static water level: ft. below land sui | rface Date 2/10/76 | /y <u>r</u> . | |
| Green | Schole | | 30 | 36 | 12. Pumping level below land | | | |
| Red C | las | | 36 | 42 | ft. after | hrs. pumpingg.p | .m. | |
| yellow | Lock | | 4/2 | 44 | 13. Water sample submitted: | mo./day | | |
| Gellow | Clay | | -4 | 50 | 14. Well head completion: | Date | - | |
| Yell re | rl | | 50 | 58 | Pitless adapter 15. Well grouted? | Inches above grade | \dashv | 1. |
| Dreen | Thale | • | - 58 | 62 | With: Neat cement | | ete - | _ - |
| Red d | lay | | 62 | 74 | 16. Nearest source of possible | e contamination: | | |
| yellow | Rock | | 74 | 78 | Well disinfected upon comple | etion?Yes | No. | 1 |
| Gellow | Clay | | 78 | 88 | 17. Pump: Manufacturer's name De Model number DA 25 | Not installed hoes-tee HP34/ Volts23 | <u>—</u>] | " |
| yellow | Rock (wa | tu) | 88 | 92 | Length of drop pipe 105 | ft. capacity 12 g.p | | €@ |
| Dreen | Shale | | 92 | 105 | Type: | Turbine | | l a . |
| Gray | Dole (Use a se | cond sheet if needed) | 105 | 115 | Jet Centrifugal | Reciprocatin | "g | حعاد |
| 18. Elevation: 0 | 19. Remarks: | | | | 20. Water well contractor's This well was drilled under m | | et | 00 |
| Topography: | | | | | is true to the best of my know | vledge and belief. | , š | 系 |
| Hill Slope | | | | | Business name | rattan Ks. 6650 | 题; | £ i≩ |
| Upland Valley | | | | | Signed Authorized rep | presentative Date // | 25 | .IK ∑∑ |