


16 x 5 = 80.

1 LOCATION OF WATER WELL: Fraction SW 1/4 NE 1/4 NE 1/4 Section Number 32 Township Number T 7 S Range Number R 6 EW
 County RILEY

Distance and direction from nearest town or city street address of well if located within city?
 2 south, 1 west of Randolph

2 WATER WELL OWNER: Steve Hargraves
 RR#, St. Address, Box # : Box 63 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Randolph, KS 66554 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL... 120' ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 99' ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL .87' ft. below land surface measured on mo/day/yr 3-27-90
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield .14 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter .8 3/4 in. to ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5" in. to 0-80 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface X 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 80 ft. to 120 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 33 ft. to 120 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole plug
 Grout intervals: From 0 ft. to 33 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? East How many feet? 110'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Clay-Brown	90	92	Shale-Yellow-loose
3	4	Limestone-loose-Yellow	92	99	Limestone-Yellow-loose
4	8	Shale-Yellow	99	114	Limestone-Yellow-hard
8	9	Limestone-Yellow	114	120	Shale-Grey
9	12	Shale-Yellow			
12	20	Shale-Red			
20	21	Shale-Yellow			
21	28	Shale-Red			
28	32	Shale-Yellow			
32	38	Limestone-Yellow			
38	41	Limestone-Yellow-loose			
41	44	Limestone-Yellow			
44	53	Shale-Yellow			
53	54	Limestone-Yellow			
54	90	Shale-Yellow			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-27-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 4-3-99 under the business name of STRADER DRILLING CO., INC. by (signature) [Signature]

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4