	WATER	WELL RECOF	RD For	m WWC-5	WC-5 KSA 82a-1212				MWB			
1 LOCATION OF WATER	VELL:	Fraction SE	SW	NE	Secti	on Number	Townst	nip Nun		1	Range Nu	\sim
County: Distance and direction from	nooroot town o	<u>¼</u>	trace of well if		1/4	23	T	7	S	R		E/W
East	Hyw 16,	Olsburg,	Kansas	iocated w	itriiri City?							
2 WATER WELL OWNER												
2 WATER WELL OWNER RR#, St. Address, Box #O: City, State, ZIP Code	ity of Ols	bury Att	n: Marvi	n John	son		Board	of Agr	riculture,	Division	of Wate	r Resource
	·				_				Number:			
LOCATE WELL'S LOCAT	TION WITH 4	DEPTH OF CO	MPLETED WE	ELL	20.	. ft. ELEVA	TION:					
AN "X" IN SECTION BO	(Dep		ater Encounter								 705	
Ī	! WE		NATER LEVEL			_						
NW	NE		test data: We									
1 !	! Est.	. Yieid	8.625 ^{We}	ell water w	as	ft. a	fter	 	hours p	umping .		gpn
* W 1			er DBE USED AS		Public water		ana 8 Air conditi			n. to Injectio		
-	WE	1 Domestic	3 Feedlot		Dil field water	,	9 Dewaterin	•		•	Specify b	oelow)
SW	SE	2 Irrigation	4 Industri				Monitoring					
	Wa	•	acteriological sa	imple subr	nitted to Dep	partment? Ye	esNo	X	If yes	s, mo/day	y/yr samį	ole was su
1 5	mitt			·			ter Well Disir				No X	
5 TYPE OF BLANK CASIN	NG USED:		5 Wrought iron	1	8 Concret	e tile	CASING	MIOL E	TS: Glue	ed 7.7.7.	Clamp	ed
1 Steel	3 RMP (SR)		6 Asbestos-Ce	ement	9 Other (s	specify below	v)		Wel	deđ		
(2)PVC 2	4 ABS	<i>1</i> / \chi	7 Fiberglass			- - <u></u>		•				
Blank casing diameter	^			SCH 4	OPVC		ft., Dia .			. in. to .		ft
Casing height above land s	_		n., weight		(Figure	lbs./ [.]	ft. Wall thickr	ness or	gauge I	No. 7.7.	:==	
TYPE OF SCREEN OR PE			5 Eiborglass		(7) PVC				stos-cem			
2 Brass	-					, ,			Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wr									11 None (open hole)			
1 Continuous slot	(3 Mill sk	ot		Wire wra	• •		9 Drilled h	oles			` '	•
2 Louvered shutter	4 Key p	unched	// ⁷	Torch cut	<i>,</i> ,		10 Other (s					
SCREEN-PERFORATED IN	ITERVALS:	From	<i>F.O.</i> fi	t. to	. <i>6</i> .0	ft., Fror	m 7777		ft.	to	· 	
SAND		From	_ ft	t. to	/ -	ft., Fror				to	· 	
GRAVE L PACK IN		From	•	t. to	. <i>60</i>	ft., Fror		• • • • • • • •			·	
C CDOUT MATERIAL.		From	·	. to	(Dearton	ft., Fron			ft.	to		ft
6 GROUT MATERIAL: Grout Intervals: From	Neat ceme	32	Cement grout	32	(3)Benton		Other 7.7.7			ft. t		
What is the nearest source							tock pens				ed water	well
1 Septic tank	4 Lateral lin		7 Pit pri	vy		11 Fuel:	•			Oil well/0		
2 Sewer lines	5 Cess poo	d	-				tilizer storage 60th			Other (sp	her (specify below)	
3 Watertight sewer lin	es 6 Seepage	pit	9 Feedy	ard			ticide storage		ntami	nated		
Direction from well?						How man	ny feet?	si				
FROM TO	<u> </u>	ITHOLOGIC L	OG	-	FROM	то		PLU	GGING	INTERV	ALS	
GL 2.00 Fi	ll, gravel							Ta1.	b 14			
	lty Clay (-				usn m n Tay	ount	waı	
25.00 29.00 C1	ayey silt								n ray	5/5/	95	
	mestone, h									J) J)		
	mestone, w	eathered										
	ale											
60.00 TD Enc	d of Boreh	ole										
						-			484			,
7 CONTRACTOR'S OR L	ANDOWNER'S	CERTIFICATIO	N. This water	well was /	(1) construct	red (2) reco	nstructed or	(3) plu	oged un	der my	iurisdictic	on and wa
completed on (mo/day/year)		5		was			rd is true to t					
	58	5	This W	ater Well					_	6/21/		
Water Well Contractor's Lice under the business name of	Associate	d Environ	mental, I	nc.		by (signat	· ^ \/ la	hus	med	nT	un	Dune
INSTRUCTIONS: Use typewrite	er or ball point pen. <u>F</u>	PLEASE PRESS FIF	MLY and PRINT cle	early. Please							Kansas De	partment
of Health and Environment, Bu												