| WATER WELL I | RECORD Form WWC-5 | KSA 82a- | 1212 ID | No | | |
|---|--|--|---|---|--------------------------|--|
| 1 LOCATION OF WATER WELL: Fraction County: CLAY 5E | 14 NW 14 5E 1 | | tion Numbe | er Towns | ship Number S | Range Number R |
| Distance and direction from nearest town or city stre | | | | | 39° 20.8 | |
| FROM TOANA: 3/4 MELR 500 2 WATER WELL OWNER: ROY HARRES | 5 | | | CP5 | 970 /5 | 806 |
| RR#, St. Address, Box # : 220 N · LPN City, State, ZIP Code : CLAY CENTS | KOLN L KS 67432_ | | | Appli | cation Number: | Division of Water Resources |
| 3 LOCATE WELL'S LOCATION WITH 4 DEPTH (| OF COMPLETED WELL | .1.B3 | ft. ELE\ | VATION: | | |
| AN "X" IN SECTION BOX: Depth(s) G | roundwater Encountered | 1 | ow land surf | ft. 2ft. 2 face measured | on mo/day/yr | 3ft. |
| NW NE WELL WAT | Pump test data: Well water | was was Public water so Dil field water | supply supply | t. aftert. after 8 Air condi 9 Dewateri | hours hours tioning 11 l | pumping gpm pumping gpm njection well Othe (Specify below) |
| W E 2 Irriga | tion 4 Industrial 7 I | Domestic (lav | vn & garden | n) 10 Monitorir | ng well | BY LUP GESHERMA |
| Was a chemitted | mical/bacteriological sample s | submitted to | Department | ? Yes No Water Well Dis | ; If yes, infected? Yes | mo/day/yrs sample was sub- |
| TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) | 5 Wrought iron 6 Asbestos-Cement | 8 Concre | | | | ed Clamped |
| 2 PVC 4 ABS | 7 Fiberglass | <i>F</i> | specify belo | | Thr | ded |
| Blank casing diameterin. to | o/B.3 ft., Dia | | in. to | | ft., Dia | ft. |
| Casing height above land surface | in., weight | | | lbs./ft. Wall | thickness or gua | ge No. <i>SDRI</i> |
| TYPE OF SCREEN OR PERFORATION MATERIA 1 Steel 3 Stainless Steel | L: 5 Fiberglass | <u>7 PV</u> | C MP(SR) | | 0 Asbestos-Cei | ment y) |
| 2 Brass 4 Galvanized Steel | 6 Concrete tile | 9 AE | | | 2 None used (c | • • |
| SCREEN OR PERFORATION OPENINGS ARE: | | ed wrapped | | 8 Saw cu | | 11 None (open hole) |
| 1 Continuous slot 3 Mill slot | | 6 Wire wrapped 7 Torch cut | | 9 Drilled holes 10 Other (specify)ft. | | |
| 2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS: From | | | 4 5 | ` | . ,, | |
| | ft. to ft. to | | | | | |
| GRAVEL PACK INTERVALS: From | ft. to | | ft., Fro | om | ft. t | oft. |
| From | ft. to | | tt., Fro | om | tt. t | ott. |
| 6 GROUT MATERIAL: 1 Neat cement | 2 Cement grout | | tenite | | | |
| Grout Intervals: From | | ft. 1 | | | | |
| · | ne nearest source of possible contamination: | | 10 Livestock pens 14 Abandoned water well | | | |
| 1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool | | · • | | el storage 15 Oil well/Gas well | | |
| 3 Watertight sewer lines 6 Seepage pit | 9 Feedyard | | | ertilizer storage (a Other) (specify below) secticide storage (b Other) (specify below) | | |
| Direction from well? | o i codyan | • | | | 'o | |
| | OGIC LOG | FROM | ТО | , , , , , , , , , , , , , , , , , , , | PLUGGING I | NTERVALS |
| O 35 SANDY CLAY | | 175 | 183 | SHALL | LARAY | |
| 35 53 GRAVBLLY SHA | מו | , - | | | | |
| 53 BB SHALE, GRAY | | | | | | |
| BB B7 LAMBSTONE | 1 1110 | | | | | |
| B9 94 SHALE, GRAY | W/ GYFSUM | | | | | |
| 94 95 LIMBSTONE | | | | | | |
| 12 100 Simoley GF-17 | | | | | | |
| 108 109 LIMPLYOWE | | | | | | |
| 131 133 LIMESONE | | | | | | |
| 133 141 SHALE LAN | , | | | | | |
| 141 142 LIMESTONE | | | | | | |
| 142 172 SHALE, GKA | 4 | | | | | |
| 172 175 LIMMESTONA | | | | | | |
| 7 CONTRACTOR'S OR LANDOWNER'S CERTIF | FICATION: This west well w | | | | | |
| completed on (mo/day/year) | | | and this | record is true to | o the best of my | knowledge and belief. Kansas |
| Water Well Contractor's Licence No | This Water | Well Record | | | y/yr) | 70106 |
| under the business name of #550CFATED | DRELLENG IN | <u>~</u> | | y (signature) | L Mayl, | 11 |
| INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRI</u> and Environment, Bureau of Water, Geology Section, 1000 SW records. Fee of \$5.00 for each <u>constructed</u> well. | | | | | | |