


1 LOCATION OF WATER WELL: Fraction E 1/2 SW 1/4 SW 1/4 Section Number 27 Township Number T 8 S Range Number R 12 E
 County: Pott. Co

Distance and direction from nearest town or city street address of well if located within city? 63 Highway + WIST 100 yds. From Emmitt 60 1 mile North on

2 WATER WELL OWNER: LAWRENCE HOCHARD
 RR#, St. Address, Box #: 10670 Highway 63
 City, State, ZIP Code: EMMITT, KS 66422
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 81 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 57 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 50 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 20 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 9 in. to 8 1/2 in. to in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No: If yes, mo/day/yr sample was submitted
 Water Well Disinfected: Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded
 Blank casing diameter 5 in. to 6 1/2 in. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface: 2 in., weight 5.4 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 31/1000's 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 SCREEN-PERFORATED INTERVALS: From 61 ft. to 81 ft. From ft. to ft. ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 81 ft. From ft. to ft. ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20 ft., From 81 ft. to Enviroclay From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 14 Livestock pens 15 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 13 Insecticide storage
 Direction from well? No E. How many feet? 125

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Top Soil			
4	26	Brown Clay			
26	27	Limestone			
27	32	Greenish Shale			
32	35	Grey Shale			
35	39	Limestone			
39	43	Brown Shale			
43	47	Limestone			
47	50	Greenish Shale			
50	53	Limestone			
53	57	Grey Shale			
57	64	Limestone (Water)			
64	75	Grey Shale			
75	78	Limestone			
78	81	Grey Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/1/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo/day/yr) 9/3/90 under the business name of Haldeman Well Drilling by (signature) Craig H. [Signature]