


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 20 Township Number T 8 S Range Number R 15 EW

Distance and direction from nearest town or city street address of well if located within city?  
2 west, 1/2 north of Mayetta

2 WATER WELL OWNER: John Meinholdt Cecil Johnson  
RR#, St. Address, Box #: 1900 N. Central 11655 166th Rd. Board of Agriculture, Division of Water Resources  
City, State, ZIP Code: Topeka, KS 66608 Mayetta, KS 66509 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 59' ft. ELEVATION: ... ft.  
Depth(s) Groundwater Encountered 1. 10' ft. 2. ... ft. 3. ... ft.  
WELL'S STATIC WATER LEVEL .8' ft. below land surface measured on mo/day/yr 7-01-96  
Pump test data: Well water was ... ft. after ... hours pumping ... gpm  
Est. Yield .1 gpm: Well water was ... ft. after ... hours pumping ... gpm  
Bore Hole Diameter .10" in. to ... ft., and ... in. to ... ft.  
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes ... No X; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  
2 PVC 4 ABS 7 Fiberglass Threaded  
Blank casing diameter 5" in. to 0-9 ft., Dia 5" in. to 19-57 ft., Dia ... in. to ... ft.  
Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258  
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
SCREEN-PERFORATED INTERVALS: From 9 ft. to 19 ft., From ... ft. to ... ft.  
From 57 ft. to 59 ft., From ... ft. to ... ft.  
GRAVEL PACK INTERVALS: From 8 ft. to 59 ft., From ... ft. to ... ft.  
From ... ft. to ... ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout intervals: From 0 ft. to 8 ft., From ... ft. to ... ft., From ... ft. to ... ft.  
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well  
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage pond  
Direction from well? south How many feet? 300'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			7-01-96 NOTE: Rich Harper gave permission to shallow grout.
3	20	Clay-Brown			
20	26	Shale-Grey			
26	33	Shale-Red			
33	59	Shale-Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-01-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 7-18-96 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Dobson

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY  
T  
R  
EW  
SEC.