

LOCATION OF WATER WELL	Fraction <u>SW</u> <u>SW</u> <u>NE</u>	Section Number	Township Number	Range Number
County: <u>JACKSON</u>	<u>SE</u> 1/4 <u>SE</u> 1/4 <u>NE</u> 1/4	<u>23</u>	T <u>8</u> (S)	R <u>15</u> (E)W

Distance and direction from nearest town or city? 1/2 E OF MAYETTA Street address of well if located within city?

WATER WELL OWNER: Lori Flewelling  
 RR#, St. Address, Box #: PO Box 55 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Mayetta 66509 Application Number:

DEPTH OF COMPLETED WELL: 60 ft. Bore Hole Diameter: 10 in. to ... ft., and ... in. to ... ft.  
 Well Water to be used as:  
 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well  
 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)  
 10 Observation well  
 Well's static water level: 15 ft. below land surface measured on JUNE month 1 day 81 year  
 Pump Test Data: Well water was ... ft. after ... hours pumping ... gpm  
 Est. Yield 1 gpm: Well water was ... ft. after ... hours pumping ... gpm

TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued  Clamped ...  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ...  
 7 Fiberglass Threaded ...  
 Blank casing dia: 5 in. to 0-13 ft., Dia: 5 in. to 33-50 ft., Dia: 5 in. to ... ft.  
 Casing height above land surface: 2.8 in., weight: 2.86 lbs./ft. Wall thickness or gauge No. 25B

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) ...  
 12 None used (open hole)  
 Screen or Perforation Openings Are:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) ...  
 Screen-Perforation Dia: 5 in. to ... ft., Dia: ... in. to ... ft., Dia: ... in. to ... ft.  
 Screen-Perforated Intervals: From 13 ft. to 33 ft., From ... ft. to ... ft., From ... ft. to ... ft.  
 From 50 ft. to 60 ft., From ... ft. to ... ft., From ... ft. to ... ft.  
 Gravel Pack Intervals: From 10 ft. to 60 ft., From ... ft. to ... ft., From ... ft. to ... ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grouted Intervals: From 0 ft. to 10 ft., From ... ft. to ... ft., From ... ft. to ... ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well  
 2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well  
 3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)  
 13 Watertight sewer lines  
 Direction from well: W How many feet: 100 ? Water Well Disinfected? Yes  No  
 Was a chemical/bacteriological sample submitted to Department? Yes  No  If yes, date sample  
 was submitted ... month ... day ... year: Pump Installed? Yes  No   
 If Yes: Pump Manufacturer's name ... Model No. ... HP ... Volts ...  
 Depth of Pump Intake ... ft. Pumps Capacity rated at ... gal./min.  
 Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on June month 1 day 1981 year  
 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182  
 This Water Well Record was completed on June month 4 day 1981 year under the business name of Strader Drilling Co., Inc. by (signature) Dale Ashen

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
	0	4	Top soil			
	4	22	Sandy clay			
	22	42	shale, grey			
	42	49	sandy shale			
	49	60	shale, grey			

ELEVATION: 1140 RM

Depth(s) Groundwater Encountered 1. 18 ft. 2. ... ft. 3. ... ft. 4. ... ft. (Use a second sheet if needed)

OFFICE USE ONLY  
T  
R  
15  
PM  
SEC.  
23  
SE 1/4  
SE 1/4  
SW 1/4  
NW 1/4