

Winchester

Not Home 7/28

10

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction SE NE NE Section Number 32 Township Number T 8 S Range Number R 19 E/W

Distance and direction from nearest town or city street address of well if located within city? 7 miles North Oskaloosa, KS. Highway 59

2 WATER WELL OWNER: Col. ROBERT DILL RR Valley Falls, KS. Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Diagram of a 36-acre section with a well location marked 'X' in the NE corner] 4 DEPTH OF COMPLETED WELL: 68 ft. ELEVATION: 1125 pm. WELL'S STATIC WATER LEVEL: 23 ft. below land surface measured on 5-5-82. Pump test data: Well water was 3 gpm at 46 ft. after 15 hours pumping. Bore Hole Diameter: 10 in. to 15 ft., and 8 1/4 in. to 68 ft. WELL WATER TO BE USED AS: 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below). Was a chemical/bacteriological sample submitted to Department? Yes. No. X. If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), 10 Observation well. CASING JOINTS: Glued X Clamped, Welded, Threaded. Blank casing diameter: 6 in. to 67 ft., Dia. Casing height above land surface: 12 in., weight lbs./ft. Wall thickness or gauge No. 0.332. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 40 ft. to 64 ft. GRAVEL PACK INTERVALS: From 15 ft. to 67 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 5 ft. to 15 ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below). Direction from well? NORTH How many feet? 60

Table with columns: FROM, TO, LITHOLOGIC LOG. Rows: 0-5 TOP SOIL, 5-30 Yellow CLAY, 30-46 SANDY YELLOW CLAY WATER AT 46, 46-50 Blue SHALE, 50-52 ROCK LIMESTONE, 52-54 GRAY SHALE, 54-60 Blue SHALE, 60-68 ROCK.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) MAY 5, 1982 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 317 This Water Well Record was completed on (mo/day/yr) 6-2-82 under the business name of WILLIAMSON Well DRIG by (signature) Francis Kame. INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.