


1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Leavenworth		NE 1/4 NW 1/4 NW 1/4		26		T 8 S		R 22 (E/W)	
Distance and direction from nearest town or city street address of well if located within city? 11101 Metropolitan - Leavenworth, Kansas									
2 WATER WELL OWNER: Amoco Oil Company									
RR#, St. Address, Box #: 8700 Indian Creek Parkway, Suite 100 Board of Agriculture, Division of Water Resources									
City, State, ZIP Code: Overland Park, Kansas 66210 Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24.5 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. Dry ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL Dry ft. below land surface measured on mo/day/yr 10/10/89 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6.0 in. to 24.5 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
Blank casing diameter 2 in. to 4.55 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface -0.25' in. weight lbs./ft. Wall thickness or gauge No. SCH 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 4.55 ft. to 23.55 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 3.5 ft. to 24.5 ft. From ft. to ft. From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0.0 ft. to 2.5 ft. From 2.5 ft. to 3.5 ft. From ft. to ft.									
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? South How many feet? 5'									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0.0 0.5 Concrete									
0.5 4.0 Lean, Sandy, Clay Olive Green, Wet with Rubble									
4.0 17.0 Lean Clay, Dark Gray - Moist									
17.0 19.0 Lean Clay, Olive Green, Moist									
19.0 22.5 Fat Clay, Mottled Gray Brown and Yellow Brown, Moist - Stiff									
22.5 24.5 Weathered Shale, Yellow Brown									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/6/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 10/30/89 under the business name of Terracon Consultants by (signature) <i>[Signature]</i>									