Location of Water Well: Fraction NW	esources ft gpm gpm ft below)
Distance and direction from nearest town or city street address of well if located within city? 2 WATER WELL OWNER: Tom's Service RR#, St. Address, Box # : 217 S 7 th Board of Agriculture, Division of Water Re Application Number: 3 LOCATE WELL'S LOCATON WITH A DEPTH OF COMPLETED WELL 17.18 ft. ELEVATION: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 WELL'S STATIC WATER LEVEL 11.17 ft. below land surface measured on molday/yr Pump test data: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. afte	gpm gpm ft below)
Board of Agriculture, Division of Water Research, KS 66048 Application Number: Application	gpm gpm ft below)
Board of Agriculture, Division of Water Recity, State, ZIP Code	gpm gpm ft below)
R#, St. Address, Box # 217 \$ 7 th Board of Agriculture, Division of Water Re Application Number: LOCATE WELL'S LOCATON WITH 4 DEPTH OF COMPLETED WELL 17.18 ft. ELEVATION:	gpm gpm ft below)
Application Number: COCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: Depth (s) Groundwater Encountered 1	gpm gpm ft below)
LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: AN "X" IN SECTION BOX: Depth (s) Groundwater Encountered 1 17.18 ft. ELEVATION:	gpm gpm ft below)
WELL'S STATIC WATER LEVEL 11.17 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Bore Hole Diameter 8 in. to 17.18 ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oll field water supply 9 Dewatering 12 Other (Specify 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr samp S TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Slank casing diameter 2 in. to 7.18 ft., Dia in. to ft., Dia in. to Casing height above land surface 0 in., weight .716 Ibs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	gpm gpm ft below)
WELL'S STATIC WATER LEVEL 11.17 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Bore Hole Diameter 8 in. to 17.18 ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oll field water supply 9 Dewatering 12 Other (Specify 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr samp Water Well Disinfected? Yes No X TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass Threaded X Iank casing diameter 2 in. to 7.18 ft., Dia in. to ft., Dia in. to Fisasing height above land surface 0 in., weight 7PE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	gpm gpm ft below)
WELL'S STATIC WATER LEVEL 11.17 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Bore Hole Diameter 8 in. to 17.18 ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oll field water supply 9 Dewatering 12 Other (Specify 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr samp Water Well Disinfected? Yes No X TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass Threaded X Iank casing diameter 2 in. to 7.18 ft., Dia in. to ft., Dia in. to Fisasing height above land surface 0 in., weight 7PE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	gpm gpm ft below)
WELL'S STATIC WATER LEVEL 11.17 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Bore Hole Diameter 8 in. to 17.18 ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oll field water supply 9 Dewatering 12 Other (Specify 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr samp Water Well Disinfected? Yes No X TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Velded 2 PVC 4 ABS 7 Fiberglass Threaded X Stank casing diameter 2 in. to 7.18 ft., Dia in. to ft., Dia in. to Casing height above land surface 0 in., weight .716 Ibs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	gpm gpm ft below)
Pump test data: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Bore Hole Diameter 8 in. to 17.18 ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr samp submitted Water Well Disinfected? Yes No X TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Islank casing diameter 2 in. to 7.18 ft., Dia in. to ft., Dia in. to casing height above land surface 0 in., weight .716 Ibs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 12 None used (open hole)	gpm gpm ft below)
Est. Yield gpm: Well water was ft. after hours pumping Bore Hole Diameter 8 in. to 17.18 ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr samp submitted Water Well Disinfected? Yes No X TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Stank casing diameter 2 in. to 7.18 ft., Dia in. to ft., Dia in. to Casing height above land surface 0 in., weight .716 Ibs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	gpm ft below)
Bore Hole Diameter 8 in. to 17.18 ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr samp submitted Water Well Disinfected? Yes No X TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Islank casing diameter 2 in. to 7.18 ft., Dia in. to ft., Dia in. to casing height above land surface 0 in., weight .716 Ibs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	below) be was
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr samp submitted Water Well Disinfected? Yes No X TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X lank casing diameter 2 in, to 7.18 ft., Dia in, to saing height above land surface 0 in., weight .716 Ibs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	le was
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr samp submitted Water Well Disinfected? Yes No X TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in, to 7.18 ft., Dia in, to diasing height above land surface 0 in., weight .716 Ibs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	le was
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr samp submitted Water Well Disinfected? Yes No X TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X lank casing diameter 2 in, to 7.18 ft., Dia in, to saing height above land surface 0 in., weight .716 Ibs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	le was
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr samp submitted Water Well Disinfected? Yes No X TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Clamp 1 Steel 2 in. to 7.18 ft., Dia in. to 1.5 in. to 1.	le was
S submitted Water Well Disinfected? Yes No District	
TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded X lank casing diameter 2 in. to 7.18 ft., Dia in. to ft., Dia in. to sasing height above land surface 0 in., weight 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X lank casing diameter 2 in. to 7.18 ft., Dia in. to ft., Dia in. to casing height above land surface 0 in., weight .716 Ibs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
2 PVC 4 ABS 7 Fiberglass Threaded X lank casing diameter 2 in, to 7.18 ft., Dia in. to ft., Dia in. to lasing height above land surface 0 in., weight .716 lbs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
2 PVC 4 ABS 7 Fiberglass Threaded X Slank casing diameter 2 in. to 7.18 ft., Dia in. to ft., Dia in. to casing height above land surface 0 in., weight .716 lbs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
casing height above land surface 0 in., weight .716 lbs./ft. Wall thickness or gauge No154 YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	ft
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
	hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
CREEN-PERFORATED INTERVALS: From 7.18 ft. to 17.18 ft. From ft. to	ft
From ft. to ft. From ft. to	
GRAVEL PACK INTERVALS: From 5.18 ft. to 17.18 ft. From ft. to	
From ft. to ft. From ft. to	ft
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
crout intervals From 0 ft. to 1 ft. From 1 ft. to 5.18 ft. From ft. to	ft
/hat is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water w	ell
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Contaminated	Site
irection from well? How many feet?	
FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0 1 Surface	
1 8 Greenish-gray Clayey silt	
8 17 Greenish-gray Silt wifine sand	
stringers	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction at	nd was
mpleted on (mo/day/yr) 10/24/2006 and this record is true to the best of my knowledge and belief. Ka	
ater Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr)	
der the business name of Woofter Pump & Well by (signature)	