		ELL RECORD FO	orm WWC-5	KSA 82a-1	1212 ID No.	MW 7			
1 LOCATION OF WATER WELL:				ion Number	,		Range Nur	Range Number	
County: Leavenworth	NW ¼	SE ¼ SE	1/4	26	т 8	8 s	R 22	(E)W	
Distance and direction from nearest to	wn or city street address	s of well if located v	vithin city?						
2 WATER WELL OWNER: Tom's RR#, St. Address, Box # : 217 S City, State, ZIP Code : Leave	7 th	48					rision of Water Re	sources	
LOCATE WELL'S LOCATON WITH					·····	n Number:			
3 AN "X" IN SECTION BOX:	DEPTH OF COM	PLETED WELL	22.4	9 ft. ELE	VATION:				
N	Depth(s) Groundwate							ft.	
	WELL'S STATIC WA	TER LEVEL 1	0.70 ft.	below land s	surface measu	red on mo/day	/yr		
NWNE		t data: Well water							
	Est. Yield	gpm: Well water	was	i 1	t. after	hours	pumping	gpm	
½ W ► E	Bore Hole Diameter	8 in. to	22.4	19	ft. and	ir	n. to	ft.	
	WELL WATER TO B 1 Domestic 3	EUSEDAS: 5 P	UDIIC Water su il field water s	ipply	8 Air con	ditioning 1 vina 1	1 Injection well 2 Other (Specify	helow)	
sw € X	2 Irrigation 4	Industrial 7 L	awn and name	an (domaeti	c) 10 Monite	nning vell	L Olidi (Opcol)	DOION)	
S	Was a chemical/bact	enological sample s	Submitted to D						
	submitted						No 2		
5 TYPE OF BLANK CASING USED:		-					d Clamp		
	(SR) 6					Weld	ted		
2 PVC 4 ABS		Fiberglass				Thre	aded X		
Blank casing diameter 2 Casing height above land surface	in. to 7.49	ft., Dia	in. to)	ft., Dia		in. to	ft.	
Casing height above land surface	0 in.,	weight	.716	lbs./ft.	Wall thickness	s or gauge No.	.154		
TYPE OF SCREEN OR PERFORATIO	N MATERIAL:		171	PVC	10 /	Asbestos-ceme			
1 Steel 3 Stainle	ess steel 5 nized steel 6	Fiberglass	8	RMP (SR)	11 (Other (specify)		İ	
2 Brass 4 Galva	nized steel 6	Concrete tile	9 .	ABS	12 1	None used (op	en hole)		
SCREEN OR PERFORATION OPENIN	IGS ARE:	5 Gauz	ed wrapped		8 Saw cut		11 None (open	hole)	
1 Continuous slot 3	Mill slot		wrapped		9 Drilled ho	oles			
2 Louvered shutter 4	Key punched	7 Torch			10 Other (s	pecify)			
SCREEN-PERFORATED INTERVALS	: From 7.4 9	9ft. to	22.49	ft. f	rom		to	ft.	
	From	ft. to		ft. F	rom	ft. 1	to	ft.	
GRAVEL PACK INTERVALS:	From 5.4 9	ft. to	22.49	ft. F	rom	ft. 1	to	ft.	
	From	ft. to		ft. F	rom	ft. 1	to	ft.	
6 GROUT MATERIAL: 1 Neat	coment 2 Cor	mont arout	2 Pant	onito	4 Other				
Grout Intervals From 0	ft. to 1	ft. From	ft to	7.49	9 ft Fro	m	ft. to	ft	
What is the nearest source of possible	contamination			10 Lives	tock pens	14 Ah	andoned water w	eli	
1 Septic tank		7 Pit privy			storage		well/ Gas well		
2 Sewer lines	5 Cess pool				•			w l	
3 Watertight sewer lines	6 Seepage pit	9 Feedyar			ticide storage		ntaminated		
Direction from well?			_	How many	•				
FROM TO CODE	LITHOLOGI	CLOG	FROM	TO		PLUGGING IN	NTERVALS		
	eenish-gray silt		1						
8 25 Gr	eenish-gray silt	y clay w/silt							
sti	ringers								
	***************************************				***************************************				
	· · · · · · · · · · · · · · · · · · ·						*****************************		
	**************************************			 			4244 · · · · · · · · · · · · · · · · · ·		
			4	ļl					
			1						
7 CONTRACTOR'S OR LANDOWNE			(1) construct	ed, (2) recor	nstructed, or (3)) plugged unde	r my jurisdiction a	nd was	
completed on (mo/day/yr)	10/24/20		and this	s record is to	rue to the best	of my knowled	lge and belief. K	ansas	
Water Well Contractor's License No.	5	54	This W	ater Well Re	cord was com	pleted on (mo/	day/yr) 1/2/	4/06	
under the business name of	Woofte	r Pump & We	i	b	v (signature)	VIII	CO HINALI	77	
INSTRUCTIONS: Please fill in blank Jackson St., Ste. 420, Topeka, Kansa	s and circle the correct a	nswers. Send three o	opies to Kansa	s Departmen	t of Health and I	Environment, Bu	reau of Water, 100	wsw	