

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Clay, Fraction: NE 1/4 NW 7/8 SE 1/4, Section Number: 4, Township Number: T 8 S, Range Number: R 30 W. Distance and direction from nearest town or city street address of well if located within city? From City Limits to 1 mile East on 24 Hwy 1/2 mile North.

2 WATER WELL OWNER: MARK SAVINIR Builder, RR#, St. Address, Box #: 1805 Pioneer Pl., City, State, ZIP Code: Clay Center, KS 67432. 3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in SE quadrant]. 4 DEPTH OF COMPLETED WELL: 140 ft. Depth(s) Groundwater Encountered (1) 112 ft. WELL'S STATIC WATER LEVEL: 100 ft. below land surface measured on mo/day/yr. Pump test data: Well water was 8.0 gpm. WELL WATER TO BE USED AS: 1 Domestic, 2 Irrigation, 3 Feedlot, 4 Industrial, 6 Oil field water supply, 7 Domestic (lawn & garden), 8 Air conditioning, 9 Dewatering, 10 Monitoring well, 11 Injection well, 12 Other (Specify below). Was a chemical/bacteriological sample submitted to Department? Yes. Water well disinfected? Yes.

5 TYPE OF CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought Iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter 5 in. to 120 ft., Diameter. Casing height above land surface 21 in., Weight 5440 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RM (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ABOVE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw Cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 120 ft. to 140 ft., From 25 ft. to 140 ft. GRAVEL PACK INTERVALS: From 25 ft. to 140 ft., From 25 ft. to 140 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 5 ft. to 25 ft., From 25 ft. to 200 ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer Storage, 13 Insecticide Storage, 14 Abandoned water well, 15 Oil well/gas well, 16 Other (specify below). Direction from well? North. How many feet? 200.

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Log entries include: 0-1 Top soil, 1-21 Brown clay, 21-23 Limestone, 23-36 Yellow shale, 36-55 Brown shale, 55-64 Limestone, 64-70 Yellow shale, 70-75 Limestone, 75-112 Brown shale, 112-140 Limestone (water).

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/20/2006 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451. This Water Well Record was completed on (mo/day/year) 11/29/2006 under the business name of Holdenman Well Drilling by (signature) Andy Holdenman.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells.