

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: CLAY Fraction: NR 1/4 NW 1/4 SW 1/4 Section Number: 15 Township Number: T 8 S Range Number: R 3 EW Distance and direction from nearest town or city street address of well if located within city? FROM CLAY CENTER; 1.5 MILES SOUTHWEST, 3/4 MILES NORTH Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: MR. STEVE DEBENHUM RR#, St. Address, Box #: 416 5th St City, State, ZIP Code: CLAY CENTER, KS 67432 3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N W E S 4 DEPTH OF COMPLETED WELL: 170 ft. Depth(s) Groundwater Encountered (1) 17.5 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL: 148 ft. below land surface measured on mo/day/yr. 1/10/07 Pump test data: Well water was ft. after hours pumping gpm Est. Yield: 100 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted. Water well disinfected? Yes X No

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass CASING JOINTS: Glued X Clamped Welded Threaded Blank casing diameter: 5 in. to 170 ft. Diameter: in. to ft. Diameter: in. to ft. Casing height above land surface: 24 in. Weight: lbs./ft. Wall thickness or guage No. SDR 21 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 170 ft. to 190 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 25 ft. to 190 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other Grout Intervals: From 3 ft. to 25 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 6 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well OPEN PASTURE Direction from well? How many feet?

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-65 CLAY BROWN, 65-74 LIMESTONE TAN, 74-88 SHALE, RED, 88-97 LIMESTONE, 97-175 SHALE, GRAY TO RED, 175-179 LIMESTONE, GRAVEL, H2O, 179-190 SHALE, GRAY

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/10/07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 760 This Water Well Record was completed on (mo/day/year) 2/1/07 under the business name of ASSOCIATED DRILLING INC by signature

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells.