WATER WELL R	ECORD Form WWC-5 Correction Change in Well Use		Division of Water Resources App. No.			Well ID	
1 LOCATION OF W.		Fraction		tion Number			
County: K; Zay	6.	NELSE 1/4 NEVA	1/4	35	T <b>8</b> (S)	R5 ZE W	
2 WELL OWNER: La	ist Name: STEINIC				where well is located		
Business: Address:  Address:  Address:							
City: RiLty	State:	5 ZIP: 6653		<del></del>			
3 LOCATE WELL WITH "X" IN	4 DEPTH OF COM	IPLETED WELL:	<i>O!</i> ft.	5 Latite	ud# 39 18.1	70 Z (decimal degrees)	
SECTION BOX:	Depth(s) Groundwater Encountered: 1) ft. Longitud						
N	Datum: WGS 84 NAD 83 NAD 27						
	WELL'S STATIC WATER LEVEL:				for Latitude/Longitude		
NW NE				GPS (unit make/model:) (WAAS enabled? ☐ Yes ☐ No)			
				□L	☐ Land Survey ☐ Topographic Map		
W E	after hours pumping gpm Well water was ft.				☐ Online Mapper:		
SW SE	often house summing						
	A 1, 1 T				6 Elevation: 12.78ft. Ground Level TOC		
S	Bore Hole Diameter:			Source:			
in. to							
7 WELL WATER TO BE USED AS: 1. Domestic: 5. □ Public Water Supply: well ID							
Household	6. ☐ Dewaterin						
🔲 Lawn & Garden	7. 🗌 Aquifer Re	echarge: well ID		☐ Cased ☐ Uncased ☐ Geotechnical			
Livestock	8. Monitoring: well ID			12. Geothermal: how many bores?			
2. ☐ Irrigation 3. ☐ Feedlot	Environmental Remediation: well ID  ☐ Air Sparge ☐ Soil Vapor Extraction				a) Closed Loop ☐ Horizontal ☐ Vertical b) Open Loop ☐ Surface Discharge ☐ Inj. of Water		
4. Industrial							
Was a chemical/bacteriological sample submitted to KDHE?  Yes No If yes, date sample was submitted:							
Water well disinfected? \( \overline{\pi} \overline{\pi} \) Yes \( \overline{\pi} \) No							
8 TYPE OF CASING USED: ☐ Steel ☐ PVC ☐ Other							
8 TYPE OF CASING USED: Steel PVC Other							
Casing height above land surface							
TYPE OF SCREEN OR PERFORATION MATERIAL:  ☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous Slot							
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)							
SCREEN-PERFORATED INTERVALS: From							
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From ft. to ft., From ft., From ft. to ft.							
Nearest source of possible contamination:							
☐ Septic Tank☐ Sewer Lines	☐ Lateral Line ☐ Cess Pool	S ☐ Pit Privy☐ ☐ Sewage Lag		Livestock Pe Fuel Storage	<del></del>	cide Storage oned Water Well	
☐ Watertight Sewer Lin				Fertilizer Sto		ell/Gas Well	
☐ Other (Specify)	• • • • • • • • • • • • • • • • • • • •	·····			-		
Direction from well?							
10 FROM TO	LITHOLOG	GIC LOG	FROM	TO	LITHO. LOG (cont.) or	LUGGING INTERVALS	
	100 1016		75	20	DANIE CAA	Notice)	
11 15	Cillow 3hd	LE	29	90	Brown Sha	<i>'</i>	
15 19	L'ALLETON C		7 0	100	UM UUN K		
18 26	Ten Shall						
26 33	Lington						
33 42	Ten Sholl		Notes:				
42 46	LIMSTON						
11 CONTRACTOR'S	TANANAKURED.	CERTIFICATION.	This water	well was F	constructed [] ====	metruoted or Daluesed	
under my jurisdiction and was completed on (mo-day-year)							
under the business name of							
INSTRUCTIONS: Send one copy to WATER WELL OWNER and retain one copy for your records. Submit fee of \$5.00 for each constructed well along with one (white) copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone (785) 296-3565.							

KSA 82a-1212

Visit us at http://www.kdheks.gov/waterwell/index.html

Revised 9/10/2012