


1 LOCATION OF WATER WELL: County: Riley Fraction: SW 1/4 SN 1/4 NW 1/4 Section Number: 9 Township Number: T 8 S Range Number: R 5 E
 Distance and direction from nearest town or city street address of well if located within city? 1 1/2 miles west of Leonardville and 1/2 mile north

2 WATER WELL OWNER: LAWRENCE KLOME
 RR#, St. Address, Box #: RR #1 Box 185
 City, State, ZIP Code: Leonardville, KS 66449
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 195 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 174 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 165 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 30 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 9 in. to 200' ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)
 2 PVC 4 ABS 7 Fiberglass Threaded.
 Blank casing diameter 5 in. to 175 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface 2 in., weight 5040 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 3/16" / 3000' 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 175 ft. to 195 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 195 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20 ft., From ft. to 250' ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? South How many feet? 250'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	27	Brown Clay	174	183	Limistoni (Water)
27	38	Limistoni	183	193	Gray Shell
38	49	Yellow Clay Shell	193	195	Limistoni
49	53	Gray Shell	195	200	Gray Shell
53	57	Limistoni			
57	74	Brown shale			
74	83	Limistoni			
83	96	Brown Shell			
96	98	Limistoni			
98	107	Yellow Shell			
107	145	Brown Shell			
145	162	Limistoni			
162	166	Brown Shell			
166	167	Limistoni			
167	174	Brown Shell			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/28/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo/day/yr) 6/27/90 under the business name of Hadden Hill Drilling by (signature) Craig A. Crompton

OFFICE USE ONLY T R EW SEC 1/4 1/4