

1 LOCATION OF WATER WELL: County: Riley Fraction: SW 1/4 NE 1/4 NE 1/4 Section Number: 26 Township Number: T 8 S Range Number: R 5 E

Distance and direction from nearest town or city street address of well if located within city? From Riley, KS 602 miles north on 24 Highway

2 WATER WELL OWNER: U.S.D. 378 Riley County High School
 RR#, St. Address, Box #: Box 326
 City, State, ZIP Code: Riley, KS 66531
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
	NW	NE	
		X	
	SW	SE	
W			E
			S

4 DEPTH OF COMPLETED WELL: 180' ft. ELEVATION: ft.
 Depth(s) Groundwater Encountered 1. 154' ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 90' ft. below land surface measured on mo/day/yr ft.
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 90 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 9 in. to 180 in. to in. to in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes..... No.....; If yes, mo/day/yr sample was submitted
 Water Well Disinfected: Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter in. to 140 in. Dia in. to in. Dia in. to ft.
 Casing height above land surface: 2 in., weight sch 40 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 25 1000
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 140 ft. to 180 ft. From ft. to ft.
 From ft. to ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 180 ft. From ft. to ft.
 From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 25 ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? WIST How many feet? 120'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil	128	154	Brown Shale
1	9	Brown Clay	154	169	Limestone = (water)
9	22	Yellow Shale	169	180	Grey Shale
22	37	Brown Shale			
37	41	Limestone			
41	46	Yellow Shale			
46	63	Greenish Shale			
63	82	Brown Shale			
82	84	Limestone			
84	95	Limestone			
95	97	Limestone			
97	112	Yellow Shale			
112	116	Limestone			
116	126	Brown Shale			
126	128	Limestone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/16/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo/day/yr) 5/22/94 under the business name of Halkerson Well Drilling by signature Craig K. CWD/PI

OFFICE USE ONLY