


1 LOCATION OF WATER WELL: County: Riley Fraction: SW 1/4 SW 1/4 SW 1/4 Section Number: 26 Township Number: T 8 S Range Number: R 6 E

Distance and direction from nearest town or city street address of well if located within city? From Riley 20 1/2 miles east for Hwy 24
* Stockdale Park Rd. 1/2 mile east to Casey Rd. 1/2 mile north

2 WATER WELL OWNER: Paul Lowe RR#, St. Address, Box #: 300 Heritage Court City, State, ZIP Code: Manhattan, KS, 66503 Application Number: Kiley Co, Permit # 95

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 36 ft. below land surface measured on mo/day/yr

Depth(s) Groundwater Encountered: 36 ft. 2. 36 ft. 3. 36 ft.

WELL'S STATIC WATER LEVEL: 36 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 15 gpm: Well water was 80 ft. after 15 hours pumping 15 gpm

Est. Yield 15 gpm: Well water was 80 ft. after 15 hours pumping 15 gpm

Bore Hole Diameter: 80 in. to 80 ft., and 80 in. to 80 ft.

WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes no No no; If yes, mo/day/yr sample was submitted

Water Well Disinfected? yes No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Clamped Clamped Welded Threaded

Blank casing diameter: 5 in. to 60 ft., Dia 60 in. to 80 ft., Dia 60 in. to 80 ft.

Casing height above land surface: 3' in., weight 50 lb 40 lbs./ft. Wall thickness or gauge No. 7 PVC 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft., From 60 ft. to 80 ft., From 60 ft. to 80 ft.

GRAVEL PACK INTERVALS: From 25 ft. to 80 ft., From 25 ft. to 80 ft., From 25 ft. to 80 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 25 ft., From 0 ft. to 25 ft., From 0 ft. to 25 ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? None close How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil			
1	11	Yellow Shale			
11	15	Limestone			
15	36	Brown Shale			
36	57	Limestone (WATER)			
57	67	Gray Shale			
67	75	Limestone			
75	80	Gray Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/29/99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo/day/yr) 8/17/99 under the business name of Haldeman Well Drilling by (signature) Craig Haldeman