


LOCATION OF WATER WELL: County: Riley Fraction NE 1/4 SE 1/4 NE 1/4 Section Number 20 Township Number T 8 S Range Number R 6 (NW)

Distance and direction from nearest town or city street address of well if located within city? 3 East & 3 North of Riley or 9779 Country Rd. Leonardville, KS.

WATER WELL OWNER: D R Grater Board of Agriculture, Division of Water Resources
Address: 9779 Country Rd. Leonardville, KS.66449 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: DEPTH OF COMPLETED WELL: 46 ft. ELEVATION:



Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL . . . 29 ft. below land surface measured on mo/day/yr 6/27/01
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield . . . 20 . . . gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter . . . 8 in. to . . . 47 ft., and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No 8; If yes, mo/day/yr sample was sub-
mitted Water Well Disinfected? Yes * No

TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued * Clamped Welded Threaded

Blank casing diameter . . . 5 in. to . . . 26 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface . . . 18 in., weight . . . 200 lbs./ft. Wall thickness or gauge No. . . 265

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From . . . 26 ft. to . . . 46 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From . . . 22 ft. to . . . 46 ft., From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From . . . 5 ft. to . . . 22 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? NE How many feet? 150

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-25 Brown Clay, 25-29 Tan Shale, 29-31 Yellow Shale, 31-46 Limestone Layers, 46-47 Gray Shale.

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/27/01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 518 This Water Well Record was completed on (mo/day/yr) 6/29/01 under the business name of Blue Valley Drilling by (signature) Eric [Signature]