

1 LOCATION OF WATER WELL: County: Riley Fraction: SE 1/4 SW 1/4 SE 1/4 Section Number: 28 Township Number: T 8 S Range Number: R 6 E/W

Distance and direction from nearest town or city street address of well if located within city? 10 mi north Hwy 24 from Manhattan/Ks
1 mile north RR 845 1 mile west Stockwell Rd 1 mile north on Frog Hollow

2 WATER WELL OWNER: Gene Lindsey
 RR#, St. Address, Box #: 6120 Blue Rock Hills Rd
 City, State, ZIP Code: Manhattan, Ks. 66503
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION: ft.

Depth(s) Groundwater Encountered: 1 54 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL: 45 ft. below land surface measured on mo/day/yr ft.

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield: 3 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
		7 Domestic (lawn & garden)	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected: Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: <u>glued</u> Clamped
<u>2 PVC</u>	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter: 5 in. to 80 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface: 2 in., weight: 526.40 lbs./ft. Wall thickness or guage No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	<u>7 PVC</u>	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	<u>3 Mill slot</u> <u>1000</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 80 ft. to 100 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 25 ft. to 100 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 25 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? None close How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil			
1	25	Brown Clay			
25	33	Limestone			
33	38	Green Shale			
38	54	Gray Shale			
54	67	Limestone (water)			
67	71	Gray Shale			
71	74	Brown Shale			
74	95	Limestone			
95	100	oily Gray Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/12/2002 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 4151 This Water Well Record was completed on (mo/day/yr) 10/18/2012 under the business name of Haldeman Well Drilling by (signature) Craig C. W. [Signature]