

**WATER WELL RECORD Form WWC-5**

Original Record  Correction  Change in Well Use

Division of Water Resources App. No. \_\_\_\_\_

Well ID \_\_\_\_\_

**1 LOCATION OF WATER WELL:**


County: Riley Co. Fraction: SE 1/4 NE 1/4 Section Number: 3 Township Number: T 8 S Range Number: R 6 E

**2 WELL OWNER:** Last Name: White First: Byron

Business Address: 1005 Troy Place  
City: St. George State: Ks ZIP: 66535

Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): From Randolph go south 2 1/2 miles to Baldwin Park Rd. Then go 1 mile East. Property on south

**3 LOCATE WELL WITH "X" IN SECTION BOX:**



**4 DEPTH OF COMPLETED WELL:** 160' ft

Depth(s) Groundwater Encountered: 1) 83' ft  
2) \_\_\_\_\_ ft 3) \_\_\_\_\_ ft, or 4)  Dry Well  
WELL'S STATIC WATER LEVEL: 80' ft  
 below land surface, measured on (mo-day-yr) 11/2019  
 above land surface, measured on (mo-day-yr) \_\_\_\_\_  
Pump test data: Well water was \_\_\_\_\_ ft after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
Well water was \_\_\_\_\_ ft after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
Estimated Yield: 1.5 gpm  
Bore Hole Diameter: 9" in. to 160' ft. and \_\_\_\_\_ in. to \_\_\_\_\_ ft.

5 Latitude: N 39° 23.390 (decimal degrees)  
Longitude: W 96° 44.317 (decimal degrees)  
Horizontal Datum:  WGS 84  NAD 83  NAD 27  
Source for Latitude/Longitude:  GPS (unit make/model: Garmin ETX 20)  
 WAAS enabled?  Yes  No  
 Land Survey  Topographic Map  
 Online Mapper

6 Elevation: 1241' ft  Ground Level  TOC  
Source:  Land Survey  GPS  Topographic Map  
 Other \_\_\_\_\_

**7 WELL WATER TO BE USED AS:**

- 1.  Domestic:
  - Household
  - Lawn & Garden
  - Livestock
- 2.  Irrigation
- 3.  Feedlot
- 4.  Industrial
- 5.  Public Water Supply: well ID \_\_\_\_\_
- 6.  Dewatering: how many wells? \_\_\_\_\_
- 7.  Aquifer Recharge: well ID \_\_\_\_\_
- 8.  Monitoring: well ID \_\_\_\_\_
- 9. Environmental Remediation: well ID \_\_\_\_\_
  - Air Sparge  Soil Vapor Extraction
  - Recovery  Injection
- 10.  Oil Field Water Supply: lease \_\_\_\_\_
- 11. Test Hole: well ID \_\_\_\_\_
  - Cased  Uncased  Geotechnical
- 12. Geothermal: how many bores? \_\_\_\_\_
  - a) Closed Loop  Horizontal  Vertical
  - b) Open Loop  Surface Discharge  Inj. of Water
- 13.  Other (specify): \_\_\_\_\_

Was a chemical/bacteriological sample submitted to KDHE?  Yes  No If yes, date sample was submitted: \_\_\_\_\_  
Water well disinfected?  Yes  No

**8 TYPE OF CASING USED:**  Steel  PVC  Other \_\_\_\_\_ CASING JOINTS:  Glued  Clamped  Welded  Threaded

Casing diameter: 5 1/2 in. to 140 ft. Diameter \_\_\_\_\_ in. to \_\_\_\_\_ ft. Diameter \_\_\_\_\_ in. to \_\_\_\_\_ ft.  
Casing height above land surface: 36 in. Weight 5ch 40 lbs/ft. Wall thickness or gauge No. \_\_\_\_\_

**TYPE OF SCREEN OR PERFORATION MATERIAL:**

- Steel  Stainless Steel  Fiberglass  PVC
- Brass  Galvanized Steel  Concrete tile  None used (open hole)

**SCREEN OR PERFORATION OPENINGS ARE:**

- Continuous Slot  Mill Slot  Gauze Wrapped  Torch Cut  Drilled Holes  Other (Specify) \_\_\_\_\_
- Louvered Shutter  Key Punched  Wire Wrapped  Saw Cut  None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 140 ft. to 160 ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

GRAVEL PACK INTERVALS: From 35 ft. to 160 ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

**9 GROUT MATERIAL:**  Neat cement  Cement grout  Bentonite  Other \_\_\_\_\_

Grout intervals: From 5 ft. to 35 ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

**Nearest source of possible contamination:**

- Septic Tank  Lateral Lines  Pit Privy
- Sewer Lines  Cess Pool  Sewage Lagoon
- Watertight Sewer Lines  Seepage Pit  Feedyard
- Other (Specify) \_\_\_\_\_
- Livestock Pens  Insecticide Storage
- Fuel Storage  Abandoned Water Well
- Fertilizer Storage  Oil Well/Gas Well

Direction from well? \_\_\_\_\_ Distance from well? \_\_\_\_\_ ft.

10 FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0	1	Top Soil	126	130	Limestone
1	2	Brown Clay	130	160	Grey Clay Shale
2	6	Yellow Shale			
6	21	Limestone			
21	52	Yellow Shale			
52	57	Limestone			
57	83	Limestone Shale			
83	102	Limestone (Water)			
102	126	Brown Shale			

Notes:

**11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:** This water well was  constructed,  reconstructed, or  plugged under my jurisdiction and was completed on (mo-day-yr) 11/1/2019 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo-day-yr) 11/3/2019 under the business name of Haldeman Well Drilling

Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.

Visit us at <http://www.kdheks.gov/waterwell/index.html>

KSA 82a-1212

Revised 1/20/2015