


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SW 1/4 Section Number 29 Township Number T 8 S Range Number R 7 E/W
 County: RILEY

Distance and direction from nearest town or city street address of well if located within city?
 8 1/4 miles east of Riley

2 WATER WELL OWNER: Larry Algott
 RR#, St. Address, Box #: 9696 Blue River Hills Rd. Ray's job Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Manhattan, KS 66503 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 200' ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 160' ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 160' ft. below land surface measured on mo/day/yr 03/02/99
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 4 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 8 3/4 in. to ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5" in. to 0-140 ft., Dia 5" in. to 180-200 ft., Dia in. to ft.
 Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. .258
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 140 ft. to 180 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 24 ft. to 200 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NORTH How many feet? 1200'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	9	Clay-Brown	96	97	Limestone-Gr 149-150 Sh-Grey
9	13	Limestone-Y	97	102	Shale-Red 150-158 Shale-Red
13	15	LS-Yellow	102	105	Limestone-Gr 158-159 LS-Y-Loose
15	21	LS-Y-Flinty	105	107	LS-Tan 159-163 Shale-Gr
21	34	LS-Grey Flinty	107	115	LS-Gr-Flinty 163-165 LS-Brown
34	38	Limestone-Gr	115	116	Shale-Gr 165-167 Shale-Gr
38	44	Shale-Gr	116	118	LS-Grey 167-172 LS-Grey
44	48	Shale-Red	118	119	Shale-Gr 172-183 Shaley LS-Gr
48	59	Limestone-Tan	119	123	LS-Grey 183-196 LS-Grey
59	74	Shale-Grey	123	132	Shale-Gr 196-200 Shale-Gr
74	81	Limestone-Gr	132	138	Shale-Red
81	87	Shale-Gr	138	143	LS-Tan-Flinty Lost circulation
87	90	Gyp	143	145	Shale-Y at 160'
90	95	Shale-Grey	145	146	LS-Yellow
95	96	Shale-Red	146	149	Shaley LS-Y

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03/02/99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 3-8-99 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Ashren