mw-2

WATER WELL RECORD	TER WELL RECORD Form WWC-5		Division of Water Resources App. No.				
1 LOCATION OF WATER WELL:	Fraction		2,000,000			Range Number	
County: Clay	14 NE 14 NW 14 NE 14			29	T 9 S	R 1	
Street/Rural Address of Well Location; if unknown, distance & dire		rection	Global	Positioning	System (GPS) in	formation:	
from nearest town or intersection: If at owner's address, check here		re 🔲. 📗	Global Positioning System (GPS) information: Latitude:				
Railroad Corridor located East of Ellis Ave. and South of County		1	Longitude: 97.3389(in decimal degrees)				
Road 404 near Oak Hill, KS		, arrey	Elevation:				
			Datum: WGS 84, NAD 83, NAD 27				
2 WATER WELL OWNER: BNSF Railway			Collection Method:  GPS unit (Make/Model: Garmin 60				
RR#, Street Address, Box #: 4515 Kansas Ave.			Digital Map/Photo, Topographic Map, Land Survey				
City, State, ZIP Code : Kansas City, KS 66106			Est. ∧ccuracy:				
3 LOCATE WELL							
with an "x" in 4 DEPTH OF COMPLETED WELL 17.5 ft.							
SECTION BOX: Depth(s) Groundwater Encountered (1)							
N WELL'S STAT	N   WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr						
Pump test data: Well water wasft. after hours pumpinggg							
NW EST. YIELDgpm. Well water wasft. after hours pumping							
w							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
Irrigation   Industrial   Domestic-lawn & garden ♥ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No							
	day/yr sample was submitt	ted.7					
1 mile  Water well disinfected? ☐ Yes ✓ No							
5 TYPE OF CASING USED: Steel					•••		
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter .2 in. to .7.5 ft., Diameter in. to ft., Diameter ft.							
Casing height above land surface. 30 in., Weight - lbs./ft., Wall thickness or gauge NoSch. 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)							
SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From .7.5 ft. to .17.5 ft., From ft. to ft.							
From							
GRAVEL PACK INTERVALS: From .5.5 ft. to .17.5 ft., From ft. to ft.							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From 2 ft to 5.5 ft, From 5 ft to 5 ft.							
What is the nearest source of possible contamination:  Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water w						(speeny delow)	
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer sto							
Direction from well		Distance fro	om well				
FROM TO LITHOLOG	IC LOG FI	ROM 1	ГО	LITHO. LO	G (cont.) <u>or</u> PLUC	GGING INTERVALS	
0 17.5 Sitty Clay							
						Name	
7 CONTRACTION OF THE STATE OF T	ICI SARIAM MAIAAN SA TAMIN SANA SANA	11 .			4_1 [7]	atad or Dulyanad	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \( \begin{align*} \text{constructed,} \propto \text{reconstructed,} \text{or plugged} \\ \text{propto   1 \text{or plugged} \\							
under my jurisdiction and was completed on (mo/day/year)?[11].1.3							
under the business name ofBelow Group	oi.iy This Water	well Rec	ora was	s completed o	n (mo/day/year).	1.4.1 60.4 1. 6	
INSTRUCTIONS: Use typewriter or ball point pen.	PLEASE PRESS FIRMLY and	PRINT clear	v. Pleasi	e fill in blanks a	nd check the correct ar	nswers. Send one copy to	
Kansas Department of Health and Environm Telephone 785-296-5524 Send one copy to WATE	ent, Bureau of Water, Geology S	Section, 1000	SW Jac	kson St., Suite 4	20, Topeka, Kansas 6	66612-1367.	

http://www.kdheks.gov/waterwell/index.html