CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:	County: Potta wa to mie Location changed to:
Section-Township-Range: 28-105-95	28-95-10E
Fraction (1/4 1/4 1/4):	NW NW NW
Other changes: Initial statements:	
Changed to:	
Comments:	
verification method: Written & legal descri	ptions, position on plat map,
	initials: DRL date: 9/8/2005

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

.1			·	WELL RECORD 1	orm WWC-5	KSA 828				
	ON OF WATE	_ 1	Fraction	د د بسرماره		ion Number 28	1	nship N		Range Number
County:	POTIANA)	rom poorest tour	WW 1/4	NN 1/4 N	W 1/4	~ 0	T	10		R 9 EW
Distance at	ria direction f	rom nearest town o	or city street ad	dress of well if located	within city?	Tom N	anigo	60	スセ	Northon
	S Wil									
_		NER: NeiL	WALL				_			
	Address, Box	/ \ \ - \ \	LILAC	A 1 ~	-				•	Division of Water Resource
City, State,			10, KS	66 547	//-				Number:	
3 LOCATE	E WELL'S LO IN SECTION	CATION WITH			 O	. ft. ELEVA	ATION:			
AN A	IN SECTION	De			2/	ft.	2		ft. 3	
ī 5	<u> </u>	ı Wi	ELL'S STATIC	WATER LEVEL 🌊	Q ft. be	elow land su	rface meas	ured on	mo/day/yr	
	- NW I	- NF								mping gpm
	- - - - - - - - - -	Es								mping gpm
•	i I	I Bo	ore Hole Diame	terin. to .	<i>40'</i>		and		in	. to
₩ -	1	ı wı	ELL WATER TO	D BE USED AS:	5 Public wate	supply	8 Air cond	ditioning	11	Injection well
7	1		1 Domestic	3 Feedlot 6	Oil field wat	er supply	9 Dewate	ring	12	Other (Specify below)
-	sw	SE	2 Irrigation	4 Industrial	Lawn and g	arden only	10 Monitor	ring wel	1 ,	
	-	i I w	as a chemical/b		-	-				, mo/day/yr sample was sul
i -	5		tted				ater Well D) No
5 TYPE C	OF BLANK C	ASING USED:		5 Wrought iron	8 Concre				INTS: Glue	Clamped
1.24	eet \	3 RMP (SR)		6 Asbestos-Cement		specify belo				ed
2 PV	(c)	4 ABS		7 Fiberglass			•			aded
Blank casi	ng diameter	in.	to 20	ft., Dia						in. to ft
		nd surface		in., weight 505 40						0
	•	R PERFORATION N		in., weight 50.2.7.9.	7 PV		./IL. YYAN UN		estos-ceme	
				5 Cibaralasa						
1 Ste		3 Stainless st		5 Fiberglass		P (SR)				
2 Bra		4 Galvanized		6 Concrete tile	9 AB	>	0.0		ne used (or	•
		ATION OPENINGS	2 \ IO	5 5 Gauze			8 Saw			11 None (open hole)
	ontinuous slot			1900 6 Wire v			9 Drilled			
1	uvered shutte		punched	20 7 Torch	///					
SCREEN-	PERFORATE	D INTERVALS:	From	· · · · · · · · · · · · · · · · · · ·						toft
			From	25	40					toft
,	GRAVEL PAC	CK INTERVALS:	From							tofi
-1			From	ft. to		ft., Fro			ft.	
_	T MATERIAL:			2 Cement grout	3 Bento					
Grout Inter				ft., From	π.					ft. to
		urce of possible co					stock pens			bandoned water well
	eptic tank	4 Lateral		7 Pit privy			storage			oil well/Gas well
ı	ewer lines	5 Cess po		8 Sewage lago	on		ilizer storag	•	16 C	Other (specify below)
ı	•	er lines 6 Seepag	e pit	9 Feedyard			cticide stor		~ <i>1</i>	
	from well?	EASI					any feet?	<u>35</u>		NITEDVALO
FROM	TO	T. (.)	LITHOLOGIC	LUG	FROM	ТО			LUGGING	NTERVALS
<i>└0,</i>	 /, 	7 100 101	<u> </u>	1						
1	2/	SAURY OF	OWN C	(WATER)						
2/	30	medium.	SANO	(WATER)						
30	40	Grey St	bale							
										47/1147
					ļ <u>.</u>					
										77.
7 CONT	BACTOR'S C	DR I ANDOMNED'S	CERTIFICATI	OM: This water well we	(1) constru	cted (2) ro	constructed	or (3)	nlugged up	der my jurisdiction and wa
_		<i>FT 1</i>	22	97						der my jurisdiction and wa nowledge and belief. Kansa
1 '	on (mo/day/		451		all December				est of my kr	2 Cowledge and delief. Kansa
1		s License No		This Water W	ell necord wa			y/yr) .		1/11/0/0
	business nar		,	CH Dr. Wing		by (sign		ra	1911	- July
I INSTRU	JCTIONS: Use tv	pewriter or ball point per	n. <u>PLEASE PRESS F</u>	IRMLY and PRINT clearly Ple	ase fill in blanks,	underline or circ	cie the correct	answers.	send top three	copies to Kansas Department
of Heal	Ith and Environm	ent, Bureau of Water, To	peka. Kansas 6662	0-0001. Telenhone: 913 ⊅ 96-5	545. Send one to	AAVIED AALI				15.