WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| County Fraction | | | | Section | number | Township number Range number | | | | |
|---|--------------------|-----------------|------|----------------|---|---|---------------|-------------------------|-----------------|------------|
| 1 Location of wells | | | | Section number | | 1 | | | | |
| 2 Distance and disc | | SW1/4 5 W/4 50 | 12 0 | <i> </i> | 1 . | T 9 | | §) R | 10 | €)W |
| 2. Distance and direction from nearest town or city: 3 E 3 N 3. Owner of well: W.I.(| | | | | | FCEE E | ichma | N | | |
| Street address of well location if in city: EF Levisville City, state, zip code: RC | | | | | | | | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | 6. Bore hole dia. in. Completion date | | | | |
| | | | | | | 7 Cable tool Rotary Driven Dug | | | | |
| | | | | | | Hollow rod Jetted Bored Reverse rotary | | | | |
| <u> </u> | | | | | | 8. Use: Domestic Public supply Industry | | | | |
| | | | | | | Irrigation Air conditioning Stock Lawn Oil field water Other | | | | |
| SW SE X - 200' | | | | | | 9. Casing: Material PC Height: Above or below | | | | |
| X | | | | | | Threaded Welded Surface Z 4 in. | | | | |
| S Mile | | | | | | RMPPVC \$4_ Weight 2.58 lbs./ft. Dia. 5_in. to 2001. depth Wall Thickness; inches or | | | | |
| 5. Type and color of material | | | | From | To Diain. to | | | ft. depth gage No. > 74 | | |
| | | | | | | 10. Screen: | Manufacturer' | s name アアエ | | |
| | TOP SOIL | | | 0 | 3 | Type <u>fv</u> | c | Dia | | |
| , ا | CIAY BROWN | | | 3 | S | Slo)/gauze Set between . | | | | |
| . ** | | | S | 32 | | ft | . and | | ft. | |
| 1 | hale, BROWN, 4 Rey | | | | | Gravel pack? | | range of mo | | o./day/yr. |
| LimesTENE , 9Rey | | | 32 | 35 | - LO ft. below land surface Date 9-20-78 | | | | | |
| Shale gray | | | | 389 | 67 | 12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m. | | | | |
| Limestone Brown | | | 67 | 70 | ft. after hrs. pumping g.p.m. | | | | | |
| Shale, Blk. gley | | | | 70 | 96 | 13. Water sample subgritted: mo./day/yr. | | | | |
| | , , | | | T | | | <u>1</u> № | | | |
| Limestonie gray | | | | 96 | 102 | 14. Well head completion: C4F — Pitless adapter 24 Inches above grade | | | | |
| Shale | , SANdy, GREY | | | 102 | 144 | 15. Well grou | | | | Concrete |
| Limes Towe Glay Shale Sandy glay | | | 190 | 200 | With: Neat cement Bentonite Conc Depth: From ft. to ft. | | | | | |
| | 31 77 | y ,,,,,, | | | | | | | | |
| | | | | | | 16. Nearest source of possible contamination: ft. 200 Direction Type Septic | | | | |
| | 374.444 | | | | | Well disinfec | ted upon com | | | No |
| | | | | | | 17. Pump: Manufacturer | 's name | N | ot installed | |
| | | | | | | Model number | | HP | | olts |
| | | V. 100 | | | | Length of drop Type: | p pipe ——— | ft. ca | pacity —— | —g.p.m. |
| | | | | | | Subme | rsible | | Turbir | 1 1 |
| | (Use a second s | heet if needed) | | | | Jet Centri | fugal | | Recipi Other | rocating S |
| 18. Elevation: 19. Remarks: | | | | | | 20. Water well contractor's certification: | | | | |
| DWNER TO INSTAL SIAL | | | | | | This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. | | | | |
| Topography: | | | | | | STRAGER DRIG CO 182 | | | | |
| Hill Slope | | | | | | Business name | | Tan | ان الحد . | cense No. |
| Upland | | | | | | Signed 2 | 0.0. | Sun | Dete | 4-24-18 |
| Valley | | | | | | Jigilea - | Authorized r | epresentativ | /e | 4 |