


LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 NW 1/4 Section Number 15 Township Number T 9 S Range Number R 12 E
 County: POTTAWATOMIE
 Distance and direction from nearest town or city street address of well if located within city? 2 1/2 S 1/2 W OF EMMETT

WATER WELL OWNER: KATH KONECY
 IR#, St. Address, Box #: 1002 N ID Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: ST. MARY'S 66536 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 DEPTH OF COMPLETED WELL: 155 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 90 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 85 ft. below land surface measured on mo/day/yr 5-3-82
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 7 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 8 in. to ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 0-80 ft. Dia 5 in. to 120-150 ft. Dia in. to ft.
 Casing height above land surface 24 in., weight 2.82 lbs./ft. Wall thickness or gauge No. 25B

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 80 ft. to 120 ft., From ft. to ft.
 From 150 ft. to 155 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 15 ft. to 155 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 5 ft. to 15 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? W How many feet? 165

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil	92	97	Shale yellow
2	9	Clay brown	97	99	Limestone grey
9	12	Limestone yellow	99	102	Shale grey
12	21	Shale yellow	102	110	Shale yellow
21	28	Limestone yellow	110	119	Shaley limestone yellow
28	59	Shale, yellow red	119	121	Shale grey
59	61	Limestone brown	121	124	shaley limestone grey
61	64	shale yellow	124	157	Shale grey
64	70	Limestone tan	157	160	Limestone grey
70	71	Shale grey			
71	72	Limestone brown			
72	75	Shale grey			
75	76	Limestone grey			
76	99	Shale, yellow			
99	92	Limestone yellow 49pm			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-3-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 192 This Water Well Record was completed on (mo/day/yr) 7-1-82
 Under the business name of STrader Drilling Co, Inc. by (signature) Dale Askren
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T 9
R 12
SEC. 15
SW 1/4
SW 1/4