


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NW 1/4 Section Number 11 Township Number T 9 S Range Number R 14 EW

Distance and direction from nearest town or city street address of well if located within city?
3 south, 5 1/2 west of Mayetta

2 WATER WELL OWNER: Ron Dick
RR#, St. Address, Box #: 9133 134th Rd. Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Mayetta, KS 66509 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 50' ft. ELEVATION: ... ft.
Depth(s) Groundwater Encountered 1. 13' ft. 2. ... ft. 3. ... ft.
WELL'S STATIC WATER LEVEL: 8' ft. below land surface measured on mo/day/yr 6-04-96
Pump test data: Well water was ... ft. after ... hours pumping ... gpm
Est. Yield 2 gpm: Well water was ... ft. after ... hours pumping ... gpm
Bore Hole Diameter: 10" in. to ... ft., and ... in. to ... ft.
WELL WATER TO BE USED AS:
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes ... No X: If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded
Blank casing diameter 5" in. to 12 ft., Dia 5" in. to 20-48 ft., Dia
Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 12 ft. to 20 ft., From ... ft. to ... ft.
From 48 ft. to 50 ft., From ... ft. to ... ft.
GRAVEL PACK INTERVALS: From 10 ft. to 50 ft., From ... ft. to ... ft.
From ... ft. to ... ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 10 ft., From ... ft. to ... ft., From ... ft. to ... ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? north How many feet? 65'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil			
1	12	Clay-Brown			
12	15	Pea Gravel-Cherty Limestone			NOTE: Permission to shallow grout from Don Taylor
15	21	Shale-Grey			6-13-96
21	25	Limestone-Grey			
25	50	Shale-Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-04-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 6-18-96 under the business name of STRADER DRILLING CO., INC. by (signature) *Don Taylor*