County: JACKSON SW 1/4 NE 1/4 NE 1/4 24 T 9 S R Distance and direction from nearest town or city street address of well if located within city?	
Distance and direction from nearest town or city street address of well if located within city?	Number
·	14 E/W
2.7/1 most of Marentto	
3 3/4 west of Mayetta	
WATER WELL OWNER: Adam Noctonick	
RR#, St. Address, Box # : Rt. 2 Box 220A Board of Agriculture, Division of W	ater Hesourc
City, State, ZIP Code : Mayetta, KS 66509 Application Number:	
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL	
Depth(s) Groundwater Encountered 130.'ft. 215.'ft. 3	
WELL'S STATIC WATER LEVEL . 12 ! ft. below land surface measured on mo/day/yr 8 – 14 -	
Pump test data: Well water was ft. after hours pumping Est. Yield 8 gpm: Well water was ft. after hours pumping	
Bore Hole Diameter12."in. to	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Speci	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? YesNoX; If yes, mo/day/yr sa	
S mitted Water Well Disinfected? Yes X No	
TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X . Cla	mped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
2 PVC 4 ABS 7 Fiberglass	
Blank casing diameter 5." in. to . 0-15 ft., Dia 5." in. to in. to	ft
Casing height above land surface7!in., weight282lbs./ft. Wall thickness or gauge No25	3
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (c	pen hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From15	
From	
GRAVEL PACK INTERVALS: From12 ft. to55 ft., from ft. to	
From ft. to ft., From ft. to GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From0ft. to12ft., From	
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned was	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas w	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage CREEK	Delow)
Direction from well? east How many feet? 50 '	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	· · · · · ·
0 15 Clay-Brown	
15 16 Fine Sand-Brown NOTE: Received perm	ssion
16 28 Clay-Brown from Don Taylor to sh	
28 30 Fine Sand-Coarse SAnd Med Gravel, Blue grout 0-12'	
30 50 Shale-Grey	
50 55 Limestone-Grey	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdi	ction and wa
ompleted on (mo/day/year)8-14-92	