


1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SW 1/4 Section Number 32 Township Number T 9 S Range Number R 14 E/W
 County: JACKSON

Distance and direction from nearest town or city street address of well if located within city?
 4 1/2 east, 1 1/2 south of Delia

2 WATER WELL OWNER: Bob Rice
 RR#, St. Address, Box # : 203 Pine Lane Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Topeka, KS 66617 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  DEPTH OF COMPLETED WELL: 60' ft. ELEVATION: ...
 Depth(s) Groundwater Encountered 1. 34' ft. 2. ... ft. 3. ... ft.
 WELL'S STATIC WATER LEVEL 5' ft. below land surface measured on mo/day/yr 6-01-93
 Pump test data: Well water was ... ft. after ... hours pumping ... gpm
 Est. Yield 15 gpm: Well water was ... ft. after ... hours pumping ... gpm
 Bore Hole Diameter 12" in. to ... ft., and ... in. to ... ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes ... No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped ...
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded ...
 2 PVC 4 ABS 7 Fiberglass Threaded ...
 Blank casing diameter 5" in. to 0-30 ft., Dia 5" in. to 40-58 ft., Dia ... in. to ... ft.
 Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. .258
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) ...
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ...
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From ... ft. to ... ft.
 From 58 ft. to 60 ft., From ... ft. to ... ft.
 GRAVEL PACK INTERVALS: From 24 ft. to 60 ft., From ... ft. to ... ft.
 From ... ft. to ... ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other ...
 Grout Intervals: From 4 ft. to 24 ft., From ... ft. to ... ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? east How many feet? 225'

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|----|--|------|----|--------------------|
| 0 | 6 | Top Soil | | | |
| 6 | 29 | Clay-Brown | | | |
| 29 | 32 | Fine Sand-Coarse sAnd-Brown | | | |
| 32 | 34 | Fine Sand-Coarse Sand-Pea Gravel-Brown | | | |
| 34 | 48 | Shale-Grey | | | |
| 48 | 51 | Limestone-Grey | | | |
| 51 | 60 | Shale-Grey | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-01-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 7-20-93 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Strader

OFFICE USE ONLY
T
R
EW
SEC