

30

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

CAA 872

1. Location of well:	County Jackson	Fraction SE 1/4 NE 1/4 SW 1/4	Section number 31	Township number T 9 S R 16 E	Range number 16 E
2. Distance and direction from nearest town or city: Street address of well location if in city:	2 5 - 1/2 E. HOYT, Kans.		3. Owner of well: Charles Habig R.R. or street: RR 1 City, state, zip code: Hoyt, Ks.		
4. Locate with "X" in section below:	Sketch map: 		6. Bore hole dia. 8 in. Completion date 11-11-77 Well depth 220 ft.		
5. Type and color of material	From	To	7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Aug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
TOP SOIL	0	3	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Clay, BROWN	3	7	9. Casing: Material PVC Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 34 in. RMP <input type="checkbox"/> PVC 46 Weight 250 lbs./ft. Dia. 5 in. to 220 ft. depth; Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth; gage No. 274		
Limestone, grey	7	9	10. Screen: Manufacturer's name Pumpco, MPI Type PVC Dia. 5 <input checked="" type="checkbox"/> 16 gauge 180 Length 4 Set between 180 ft. and 220 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 3/8 x 1/2		
Shale, grey	9	99	11. Static water level: <input type="checkbox"/> mo./day/yr. 160 ft. below land surface Date 11-11-77		
Limestone, grey, shale, grey	99	68	12. Pumping level below land surfaces: ____ ft. after ____ hrs. pumping ____ g.p.m. ____ ft. after ____ hrs. pumping ____ g.p.m. Estimated maximum yield 10 g.p.m.		
Shale, grey	68	88	13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date _____		
Shale, sandy, grey	88	190	14. Well head completion: CAP <input type="checkbox"/> Pitless adapter 24 inches above grade		
SANDSTONE, grey	190	223	15. Well grouted? <input checked="" type="checkbox"/> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 5 ft. to 15 ft.		
			16. Nearest source of possible contamination: 150 ft. W Direction W Type Lagoon Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
			17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name _____ Model number _____ HP _____ Volts _____ Length of drop pipe _____ ft. capacity _____ g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation: 1100	19. Remarks: OWNER TO INSTALL SLAB		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Stader Oil & Gas Inc 182 Business name License No. _____ Address RR 1 Hoyt, Ks Signed Dale Peterson Date 11-14-77 Authorized representative		

T 9 S R 16 E Sec 31 NE 1/4 SW 1/4