


1 LOCATION OF WATER WELL: County: **JACKSON** Fraction: **SE 1/4 SW 1/4 NE 1/4** Section Number: **30** Township Number: **T 9 S** Range Number: **R 16 EW**

Distance and direction from nearest town or city street address of well if located within city?  
**1 1/2 E 1/2 S of Hoyt**

2 WATER WELL OWNER: **Robert Noller**  
 RR#, St. Address, Box #: **10620 T. Rd** Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: **Hoyt, KS 66440** Application Number: **2 140-160 5gpm**

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  DEPTH OF COMPLETED WELL: **180** ft. ELEVATION: **180** ft.  
 Depth(s) Groundwater Encountered: 1. **100-120 2gpm** 2. **120-140 2gpm** 3. **160-180 7gpm**  
 WELL'S STATIC WATER LEVEL: **90** ft. below land surface measured on mo/day/yr **7-15**  
 Pump test data: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
 Est. Yield: **1.5** gpm: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm  
 Bore Hole Diameter: **8 3/4** in. to **1.80** ft., and \_\_\_\_\_ in. to \_\_\_\_\_ ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic  3 Feedlot  6 Oil field water supply  9 Dewatering  12 Other (Specify below)  
 2 Irrigation  4 Industrial  7 Lawn and garden only  10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes \_\_\_\_\_ No ; If yes, mo/day/yr sample was submitted \_\_\_\_\_  
 Water Well Disinfected?  Yes  No

5 TYPE OF BLANK CASING USED:  
 1 Steel  3 RMP (SR)  6 Asbestos-Cement  9 Other (specify below)  Welded \_\_\_\_\_  
 2 PVC  4 ABS  7 Fiberglass \_\_\_\_\_  Threaded \_\_\_\_\_  
 Blank casing diameter: **5"** in. to **200** ft., Dia. \_\_\_\_\_ in. to \_\_\_\_\_ ft., Dia. \_\_\_\_\_ in. to \_\_\_\_\_ ft.  
 Casing height above land surface: **24** in., weight **Sch 40** lbs./ft. Wall thickness or gauge No. \_\_\_\_\_  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel  3 Stainless steel  5 Fiberglass  7 PVC  10 Asbestos-cement  
 2 Brass  4 Galvanized steel  6 Concrete tile  9 ABS  12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot  3 Mill slot  6 Wire wrapped  9 Drilled holes  
 2 Louvered shutter  4 Key punched  7 Torch cut  10 Other (specify) \_\_\_\_\_  
 SCREEN-PERFORATED INTERVALS: From **140'** ft. to **180** ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 GRAVEL PACK INTERVALS: From **24** ft. to **200** ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

6 GROUT MATERIAL:  1 Neat cement  2 Cement grout  3 Bentonite  4 Other \_\_\_\_\_  
 Grout Intervals: From **24** ft. to **4** ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft., From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank  4 Lateral lines  7 Pit privy  10 Livestock pens  14 Abandoned water well  
 2 Sewer lines  5 Cess pool  8 Sewage lagoon  11 Fuel storage  15 Oil well/Gas well  
 3 Watertight sewer lines  6 Seepage pit  9 Feedyard  12 Fertilizer storage  16 Other (specify below) \_\_\_\_\_  
 13 Insecticide storage \_\_\_\_\_  
 Direction from well? **E** How many feet? **150**

FROM		TO		LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	11	11	16	Shaley - Yellow			
11	16	16	30	Limestone - Dr			
16	30	30	34	Shale - Dr			
30	34	34	40	LS - Dr			
34	40	40	47	Shale - Dr			
40	47	47	51	LS - TAN			
47	51	51	101	Shale - Dr			
51	101	101	115	sandy shale - Dr			
115	179	179	200	SS - Dr			
179	200	200		Shale - Dr			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  (1) constructed,  (2) reconstructed, or  (3) plugged under my jurisdiction and was completed on (mo/day/year) **7-15-94** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **174** This Water Well Record was completed on (mo/day/yr) **7-21-94** under the business name of **Brewer Inc** by (signature) **John S. Brewer**