WATER WELL RECORD Form WWC-5	Division of Water Resources App. No. Weil ID
☑ Original Record ☐ Correction ☐ Change in Well Use  1 LOCATION OF WATER WELL: Fraction	Resources App. No. Well ID  Section Number Township Number Range Number
	4 NW 43W 4 9 T 9 S R 17 DE W
2 WELL OWNER: Last Name: First:	Street or Rural Address where well is located (if unknown, distance and
Business: USACE Kansas City District	
Address: 12th Ct	
Address: City: Kansas City State: Mo ZIP: 64	106 Platte Rd- Valley Falls Ks.
1.2 7.00,000,000,000 1 6	
WITTH "Y" IN 4 DEPTH OF COMPLETED V	WELL:35.5 ft. 5 Latitude 39.279722,(decimal degrees)
SECTION BOX: Depth(s) Groundwater Encountered:	1) 26 ft. Longitude:95 = 53 [665] (decimal degrees)
2) ft. 3) ft. well's static water level:	
below land surface, measured on	Bourto Is, Butters and A
above land surface, measured on	
Pump test data: Well water was	U.A ft. ☐ Land Survey ☐ Topographic Map
W x after hours pumping	
SWSE Well water was hours pumping	
Estimated Yield:gpm	6 Elevation:
S Bore Hole Diameter:	35.5. ft. and Source: Land Survey GPS Topographic Map
i milei n. to	
7 WELL WATER TO BE USED AS:	WD 40 Flow 1997 - 0 - 1 - 1
1. Domestic: 5. ☐ Public Water Supply: w ☐ Household 6. ☐ Dewatering: how many	
☐ Household 6. ☐ Dewatering: how many ☐ Lawn & Garden 7. ☐ Aquifer Recharge: well	
Livestock 8. Monitoring: well ID	
2. Irrigation 9. Environmental Remediation	
3. Feedlot Air Sparge So	
4. Industrial Recovery Injustrial	
Was a chemical/bacteriological sample submitted to KDHE? Tes I No If yes, date sample was submitted:	
Water well disinfected?  Yes No	
8 TYPE OF CASING USED: ☐ Steel ☐ PVC ☐ Other CASING JOINTS: ☐ Glued ☐ Clamped ☐ Welded ☐ Threaded	
Casing diameter	
TYPE OF SCREEN OR PERFORATION MATERIAL:	
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)	
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
□ Continuous Slot □ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify)	
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)  SCREEN-PERFORATED INTERVALS: From	
GRAVEL PACK INTERVALS: From .3.5.5ft. to .2.2.0ft., From	
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other	
Grout Intervals: From 2.6.0 ft. to 14.0 ft., From ft. to ft., From ft. to ft.	
Nearest source of possible contamination:	
	it Privy
	ewage Lagoon
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Fe	eedyard
Direction from well? Distance	e from well? ft.
10 FROM TO LITHOLOGIC LOG	FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 1.5 Topso,1	
1.5 12' SII+ Clay Gravel	
12 14 Casel 1. C. acal	
33 34.5 Silt Clay 6 Forces	
34.5 35.5 Shala.	Notes:
ivotes:	
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **Constructed, **Constructed*, or ** plugged	
under my jurisdiction and was completed on (mo-day-year) 92/21/2020 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 597 This Water Well Record was completed on (mo-day-year) 23/1/2/2020 under the business name of Cascade Driffing L. Signature	
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,	
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367, M	(ail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.
	KSA 82a-1212 Revised 7/10/2015



Figure 2. Site Features and Proposed Well Locations.

Base map source - ESRI Digital Globe

