

51

VBRT

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

add ccd

1. Location of well: County Jefferson		Fraction SE 1/4 SE 1/4 SW 1/4		Section number 21		Township number T 9 S R 19 E/W		Range number			
2. Distance and direction from nearest town or city: 1.5 N .4 E				3. Owner of well: JACK MILLS							
Street address of well location if in city: OF OSKALOOSA				R.R. or street: RR 1							
				City, state, zip code: OSKALOOSA, KS 66066							
4. Locate with "X" in section below:				Sketch map:				6. Bore hole dia. 8 in. Completion date 7-26-79			
								Well depth 100 ft.			
								7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary			
								8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other			
								9. Casing: Material PVC Height: <input checked="" type="checkbox"/> Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 29 in. RMP <input type="checkbox"/> PVC 94 Weight 2.82 lbs./ft. Dia. 5 in. to 100 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 258			
5. Type and color of material				From		To		10. Screen: Manufacturer's name Pumpco MPF			
TOP SOIL				0		6		Type PVC Dia. 5			
Clay, brown				6		34		<input checked="" type="checkbox"/> Gauze 1020 Length 30			
Limestone, brown, water bearing				34		35		Set between 30 ft. and 60 ft.			
shale grey				35		79		Gravel pack? <input checked="" type="checkbox"/> Size range of material 10/20/40			
Lime grey				79		83		11. Static water level: <input type="checkbox"/> mo./day/yr. 35 ft. below land surface Date 7-26-79			
shale, grey				83		100		12. Pumping level below land surfaces: ____ ft. after ____ hrs. pumping ____ g.p.m. ____ ft. after ____ hrs. pumping ____ g.p.m. Estimated maximum yield 40 GPH g.p.m.			
								13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date			
								14. Well head completion: CAP <input checked="" type="checkbox"/> Pitless adapter 29 Inches above grade			
								15. Well grouted? <input checked="" type="checkbox"/> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.			
								16. Nearest source of possible contamination: ft. 100 Direction E Type Creek Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No			
								17. Pump: <input type="checkbox"/> Not installed Manufacturer's name JACO 221 Model number 5546 HP 1/2 Volts 220 Length of drop pipe 90 ft. capacity 4 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other			
								20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. STRAKER DRILG CO INC 182 Business name License No. Address RT 1 HOLTON, KS 66436 Signed DAVE BASKIN Date 7-30-79 Authorized representative			
18. Elevation: 983				19. Remarks: OWNER TO INSTALL SIB							
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input checked="" type="checkbox"/> Valley											

9
190
21
1/4 SE SE SW

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

BR clear = 1046
949
948

51

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

Recheck elev. - probably 980 not 1080
 cc'd OSL
 cddt

recheck & location on quad

WATER WELL RECORD
 KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
 (Water well Contractors)
 Topeka, Kansas 66620

1. Location of well: County JEFFERSON		Fraction SE 1/4 SE 1/4 SW 1/4		Section number 21	Township number T 9 S R 19 E/W	Range number
2. Distance and direction from nearest town or city: 1.5 N .4 E				3. Owner of well: JACK MILLS		
Street address of well location if in city: OF OSKALOOSA				R.R. or street: P.R. 1		
				City, state, zip code: OSKALOOSA, KS. 66066		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 8 in. Completion date 7-26-79		
				Well depth 100 ft.		
				7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
				8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
				9. Casing: Material PVC Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 29 in. RMP <input type="checkbox"/> PVC 92 Weight 282 lbs./ft. Dia. 5 in. to 100 ft. depth; Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth; gage No. 258		
5. Type and color of material				10. Screen: Manufacturer's name PUMPCO MPI		
Top SOIL				Type PVC Dia. 5		
Clay, brown				Sieve/gauze 1020 Length 30		
Limestone, brown, water bearing				Set between 30 ft. and 60 ft.		
shale grey				Gravel pack? <input checked="" type="checkbox"/> Size range of material 1020 x 60		
Lime grey				11. Static water level: 35 ft. below land surface Date 7-26-79		
shale, grey				12. Pumping level below land surfaces: _____ ft. after _____ hrs. pumping _____ g.p.m. _____ ft. after _____ hrs. pumping _____ g.p.m. Estimated maximum yield 40 gph		
				13. Water sample submitted: _____ mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date _____		
				14. Well head completion: cap <input checked="" type="checkbox"/> Pitless adapter 29 inches above grade		
				15. Well grouted? <input checked="" type="checkbox"/> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination: ft. 100 Direction E Type Stream Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: _____ Not installed Manufacturer's name JACOBI 221 Model number 5546 HP 1/2 Volts 220 Length of drop pipe 90 ft. capacity 4 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. STRADER DRILLING CO INC 182 Business name License No. _____ Address RT 1 HOLTAN, KS 66436 Signed Dale Ashken Date 7-30-79 Authorized representative		
18. Elevation: 1080		19. Remarks: OWNER TO INSTALL SIB				
Topography: 983						
<input type="checkbox"/> Hill						
<input type="checkbox"/> Slope						
<input type="checkbox"/> Upland						
<input checked="" type="checkbox"/> Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

BR elev = 1046 Z = 1045

T 9 S R 19 E/W
 Sec 21
 SE SE SW
 1/4 1/4 1/4