. ~		R WELL RECORD Fo		KSA 82a-12			_
1 LOCATION OF WATER W				on Number	Township Number	Range Number	_
County: Jeffers	on NW 1/4		1/4	33	т 9 s.	R 19	티
Distance and direction from no	earest town or city street ad	dress of well if located v 10152 US Hwy 59		a, KS			
2 WATER WELL OWNER:	Jackson Farmers, I	nc.					
RR#, St. Address, Box # : PO Box 191					Board of Agriculture, Division of Water Resources		
City State ZIP Code Holton, KS 66436-0191					Application Number:		
3 LOCATE WELL'S LOCATO	ON WITH 4 DEPTH OF C	OMPLETED WELL	15	ft. ELEVA	ATION:	998.48	
N	Depth(s) Ground	water Encountered 1.5	6.5	ft.	2ft	. 3 F ay/yr 01/15/15	OFFICE
↑ X	WELL'S STATIC	WATER LEVEL	3.97 ft. b	elow land su	rface measured on mo/d	ay/yr 01/15/15	☆
NWN	E Pump	test data: Well water	was	Ft.	after hou	s pumping Gpn	n 🚞
	Est. Yield	Gpm: Well water	was	Ft.	after Hou	rs pumping	n m̃
₩ W	E Bore Hole Diame	ter 8.5 In. to	15	1	ft. and	in. to F	t. 💆
SW SE	WELL WATER T	O BE USED AS: 5 P 3 Feed lot 6 O	ublic water su il field water s	pply upply	8 Air conditioning 9 Dewatering	11 Injection well 12 Other (Specify below)	두 ' ,
	2 Irrigation	4 Industrial 7 La	awn and garde	en (domestic)	10 Monitoring well	MW-1	
*	1 (es, mo/day/yr sample was	
S	Submitted	,			er Well Disinfected? Yes	1/	
5 TYPE OF BLANK CASING	USED:	5 Wrought Iron	8 Concre	te tile	CASING JOINTS: G	ued Clamped	
<u> </u>	3 RMP (SR)					and the second s	-
	, , , , ,	7 Fiberglass			•	readed X	
2 FVC	4 Ab3	Ft.,					
Blank casing diameter	2 in. to 5	Dia	In. to)	ft., Dia	in. toft	
Casing height above land surf	ace FLUSH	In., weight S	CH 40	Lbs./ft.	Wall thickness or gauge	No.	
TYPE OF SCREEN OR PERF				PVC	10 Asbestos-ce	ment	
1 Steel	3 Stainless steel	5 Fiberglass	8 F	RMP (SR)	11 Other (speci	fy)	
2 Brass	4 Galvanized steel	Concrete tile	9 A	ABS	12 None used (open hole)	'
SCREEN OR PERFORATION			ed wrapped		8 Saw cut	11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire	vrapped		9 Drilled holes		
2 Louvered shutter	4 Key punched	7 Torch			10 Other (specify)		
SCREEN-PERFORATED INT						ft. toft	
	From	ft. to		ft. Fr	om	ft. toF	t. 🔻
SAND PACK INTERV	ALS: From	4 ft. to	15	ft. Fr	om	ft. toF	t.
	From	ft. to		ft. Fr	om	ft. to F	t.
6 GROUT MATERIAL:	1 Neat cement 2	Cement grout	3 Bento	onite 4	1 Other		
	0.5	Ft.	Ft.				
Grout Intervals From2		From3	to			ft. toft	•
What is the nearest source of	•	7 By			ock pens 14		
1 Septic tank	4 Lateral lines	7 Pit privy		11 Fuel st	- ·	Oil well/ Gas well	_
2 Sewer lines	5 Cess pool	8 Sewage	•	12 Fertiliz		Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Contaminated Site							ŀ
Direction from well?			T	How many fo			\dashv
		OGIC LOG	FROM	то	PLUGGING	SINTERVALS	ى ا
0 1	Topsoil						SE SE
1 6.5	Silty Clay						_
6.5 15 TD	Sandy Clay End of Borehol	Δ	-				\dashv
10 10	Lift of potential	<u> </u>					\dashv
							7
						,	_
				ļ			_
				 			-
							-
			+	 			\dashv
7 CONTRACTOR'S OR LAN	IDOWNER'S CERTIFICATI	ON. This water well wa	s (x) construct	ted. (2) recon	structed, or (3) plugged	under my jurisdiction and w	\dashv
						ledge and belief. Kansas	
Completed on (mo/day/yr)	U1/U	585	This MA	ater Well Dog	ord was completed on fr	no/day/yr) 02/05/15	
Water Well Contractor's Licen	Jeencist	ed Environment			(signature) Bradley		
under the business name of INSTRUCTIONS: Please	fill in blanks and circle the corr	ect answers. Send three	opies to Kansa	s Department	of Health and Environment	Agreau of Water, Topeka,	\dashv
Kansas 66620-0001. Tele	phone: 913-296-5545. Send o	one to WATER WELL OW	NER and retain	one for your r	ecords.	affaluse -	