USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215 Sent to Leonard K

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

		,					1		
Location of well:	County	Fraction	NW S	SW	Section	number	Township number	Range number	
Location of well:	LEAVENWORTH	1/4	SW1/4 S			}		R 23	EAH
2. Distance and direc	ction from nearest town or city:	1 m; 5.1	<i>E</i> .	1	er of well	: (1	TY OF LEAVEN	JOKTH	
Street address of well	location if in city:			R.R. or		ode.	LEAVENWORTH,	K5	
4. Locate with "X" i	in section helaw:	Sketch map:	····				6. Bore hole dia. 54 in.		
N			M15	· ·			Well depth 69 fr.	9-6-77	8-10-
- Sonn					RIVER		7 Cable tool Rotary		
NW NE							Hollow rod Jetted Bored Reverse rotary		
w	E C	/;	œ		. ,-	7-7	8. Use: Domestic Pu	blic supply Inc r conditioning Sta	
· i);					Lawn Oi		ther
SW	× 1	1'i			1		9. Casing: Material STEEL		
<u> </u>		D. ZX.	COAC		10	2	Threaded Welded RMP PVC		
1 M	/ 1		1		.,		Dia. 26 in. to 49 ft. dep	h Wall Thickness; in	ches or
5. Type and color of	material				From	То	Dia in. to ft. dept		
					·		10. Screen: Manufacturer's n		
TOPSOIL					0			Dia. 26" Length 20	
GROWN 5	ILTY CLAY				/	6	Slot/gauze	Length <u>20</u> ft. and <u>69</u>	ft.
_					1	10	ft. o	nd	ft.
TRULIN 5AI	NOY SILT				6		Gravel pack? <u>YES</u> Size rail 11. Static water level:		./day/yr.
SRAY SAI	NOY SILT				10	20	11. Static water level: 11. B ft. below land sur		122
GRAY MEDIUM TO FINE SAND					20	28 <u>6</u>	12. Pumping level below land surfaces:		
					286	42	22.4 ft. after 4 hrs. pumping 1050 g.p.m. 22.4 ft. after 8 hrs. pumping 1050 g.p.m.		
GRAY FINE TO VERY FINE SAND					1		Estimated maximum yield	2000	_g.p.m.
GRAY MEDIUM TO COARSE SAND WITH GRAVEL					42	55	13. Water sample submitted:mo./day/yrYes No Date 9/12/29		
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		white	GRAVEL	Bound	55	69	14. Well head completion:	. /	
			<u> </u>	,				6 triches above	grade
		***************************************			 		15. Well grouted? YES	D	C
			· · · · · · · · · · · · · · · · · · ·				With: V Neat cement ft. to .	ZO ft.	Concrete
							14. Negrest source of possible	contamination	· · ·
		· · · · · · · · · · · · · · · · · · ·			1		ft. 300 Direction A Well-disinfected upon comple		No.
							17. Pump:	Not installed	
							Manufacturer's name LA	INE & BOWL	EK
							Model number 11" BHC Length of drop pipe 0	ft. capacity 200) g.p.m.
							Type:	/	
					-		Submersible	Turbing	-
(Use a second sheet if needed)							Centrifugal	Other	22.1119
18. Elevation: A	19. Remarks:	7-	,	,			20. Water well contractor's		-
760 N	WELL #5	-) ;	#	6			This well was drilled under m is true to the best of my know	•	s report
Topography:	, —	1		1.	0.4	()	LAYNE - WEST	ERN 19	19
Hill Slope	- Two &	oso	are 1	labe	lle	2	Business name Address 1010 W	Lie	10.
Topography: Hill Slope Upland Juo log are lab							Signed Authorized representative Date 1-12-7		
Valley				<i>~</i> .			Authorized rep	resentative	/
	ue and pink copies to the Department	of Health and	Environment					Form V/V	VC-5
BRE	11-1								₩,