


1 LOCATION OF WATER WELL: County: Riley Fraction: NW 1/4 NW 1/4 SW 1/4 Section Number: 13 Township Number: T 9 S Range Number: R 6 E W

Distance and direction from nearest town or city street address of well if located within city? From Manhattan to North West 7 miles on 24 Hwy to 76th Ave. + 6 1/2 Miles South

2 WATER WELL OWNER: Gary McCLain
 RR#, St. Address, Box #: 2053 Braughton Rd.
 City, State, ZIP Code: Clay Center, KS 67432
 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 140 ft. ELEVATION: 140



4 DEPTH OF COMPLETED WELL: 140 ft. ELEVATION: 140
 Depth(s) Groundwater Encountered: 1 80 ft. 2 93 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 80 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 1 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded

Blank casing diameter 5 in. to 120 ft. Dia in. to ft. Dia in. to ft.
 Casing height above land surface 2' in., weight Sch. 40 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 11 None (open hole) 10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From 120 ft. to 140 ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 140 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 25 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: NONE CLOSE
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top Soil			
1	13	Brown Clay			
13	57	Yellow Shale			
57	75	Limestone			
75	81	Grey Shale			
81	86	Limestone			
86	93	Tan Shale			
93	101	Limestone (WATER)			
101	128	Brown Shale			
128	140	Limestone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/10/2002 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 451 This Water Well Record was completed on (mo/day/yr) 10/19/2002 under the business name of Haldeman Well Drilling by (signature) Gary McCLain