USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County	Fraction	Section number	Township number	Range number
	RILEY	NW 1/4 SE 1/4 NW 1/4	36	T 9 S	R 6 E/W

2. Distance and direction from nearest town or city: 1/4 Mi. North of KEATS, KS.
Street address of well location if in city:

3. Owner of well: KERMIT PETERSON
R.R. or street: RT. 1
City, state, zip code: MANHATTAN, KS. 66502

4. Locate with "X" in section below: Sketch map:

N
NW NE
W E
SW SE
S
1 Mile 1 Mile

6. Bore hole dia. 8 in. Completion date
Well depth 94 ft. 11-2-82

7. ✓ Cable tool __ Rotary __ Driven __ Dug
__ Hollow rod __ Jetted __ Bored __ Reverse rotary

8. Use: ✓ Domestic __ Public supply __ Industry
__ Irrigation __ Air conditioning __ Stock
__ Lawn __ Oil field water __ Other

9. Casing: Material PVC Height: (above) or below
Threaded ___ Welded ___ Surface 24 in.
RMP ___ PVC 9L Weight 2.83 lbs./ft.
Dia. 5 in. to 94 ft. depth Wall Thickness: inches or
Dia. ___ in. to ___ ft. depth gage No. 258

5. Type and color of material	From	To
ROCKY TOP SOIL	1	15
WHITE ROCK	15	23
YELLOW CLAY	23	26
YELLOW ROCK	26	30
YELLOW CLAY	30	39
GREEN SHALE	39	45
YELLOW ROCK (LOTS OF WATER)	45	51
GRAY SHALE	51	60
GRAY ROCK	60	64
GRAY SHALE	64	84
BLUE SHALE	84	94
(Use a second sheet if needed)		

10. Screen: Manufacturer's name PUMPCO
Type PVC Dia. 5 IN
(Slot) gauze 80 Length 15 FT
Set between 45 ft. and 60 ft.
___ ft. and ___ ft.
Gravel pack? ✓ Size range of material 1/4 IN.

11. Static water level: mo./day/yr.
42 ft. below land surface Date 11-2-82

12. Pumping level below land surfaces:
___ ft. after ___ hrs. pumping ___ g.p.m.
___ ft. after ___ hrs. pumping ___ g.p.m.
Estimated maximum yield BAIL TEST 20 g.p.m.

13. Water sample submitted: mo./day/yr.
__ Yes ✓ No Date

14. Well head completion: CAP
__ Pitless adapter 24 Inches above grade

15. Well grouted? ✓
With: ✓ Neat cement __ Bentonite __ Concrete
Depth: From 5 ft. to 15 ft.

16. Nearest source of possible contamination:
ft. 100 Direction EAST Type SEPTIC
Well disinfected upon completion? ✓ Yes __ No

17. Pump: ✓ Not installed
Manufacturer's name
Model number HP Volts
Length of drop pipe ft. capacity g.p.m.
Type:
__ Submersible __ Turbine
__ Jet __ Reciprocating
__ Centrifugal __ Other

T 9 R 6 E/W Sec 36 1/4 NW 1/4 SE 1/4 NW 1/4

18. Elevation:
Topography:
X Hill
__ Slope
__ Upland
__ Valley

19. Remarks:

20. Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
RAY ENSLEY DRILLING 202
Business name License No.
Address RT. 6 MANHATTAN
Signed [signature] Date 11-2-82
Authorized representative

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

MI-1023