

SE NW NE SW-KGS DRL

WATER WELL RECORD Form WWC-5

Original Record Correction Change in Well Use

Division of Water Resources App. No.

Well ID

1 LOCATION OF WATER WELL: County: Riley Fraction: NE 1/4 NE 1/4 SW 1/4 Section Number: 28 Township Number: T 9 S Range Number: R 7 E W

2 WELL OWNER: Last Name: Jess & Danielle Woodard Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here:
 Business: 5275 Marlett
 Address: 5275 Marlett
 Address: Manhattan, KS 66503
 City: Manhattan State: KS ZIP: 66503

3 LOCATE WELL WITH "X" IN SECTION BOX:
 N

	X		

 W E
 S
 1 mile

4 DEPTH OF COMPLETED WELL: 140 ft.
 Depth(s) Groundwater Encountered: 1) 84 ft.
 2) ft. 3) ft., or 4) Dry Well
 WELL'S STATIC WATER LEVEL: 73 ft. 2/12/2024
 below land surface, measured on (mo-day-yr).....
 above land surface, measured on (mo-day-yr).....
 Pump test data: Well water was ft.
 after hours pumping gpm
 Well water was ft.
 after hours pumping gpm
 Estimated Yield: 1 gpm
 Bore Hole Diameter: 4 in. to 160 ft. and
 in. to ft.

5 Latitude: N 39° 14.330 (decimal degrees)
 Longitude: W 096° 39.390 (decimal degrees)
 Horizontal Datum: NGS 84 NAD 83 NAD 27
 Source for Latitude/Longitude:
 GPS (unit make/model: GARMIN E TRX 20)
 (WAAS enabled? Yes No)
 Land Survey Topographic Map
 Online Mapper:

6 Elevation: 1346 ft. Ground Level TOC
 Source: Land Survey GPS Topographic Map
 Other

7 WELL WATER TO BE USED AS:
 1. Domestic:
 Household
 Lawn & Garden
 Livestock
 2. Irrigation
 3. Feedlot
 4. Industrial
 5. Public Water Supply: well ID

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded
 Casing diameter 5 in. to 140 ft., Diameter in. to ft., Diameter in. to ft.
 Casing height above land surface 21 in. Weight sch 40 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel Stainless Steel Fiberglass PVC Other (Specify)

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other
 Grout Intervals: From 5 ft. to 33 ft., From ft. to ft., From ft. to ft.
 Nearest source of possible contamination: None Close
 Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage
 Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well
 Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well
 Other (Specify)

10 FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0	1	Top Soil	84	93	Limstone (water)
1	2	Yellow shale	93	113	Grey shale
2	4	Limstone	113	118	Limstone
4	6	Yellow shale	118	125	Grey shale
6	16	Limstone	125	135	Limstone
16	33	Grey shale	135	160	Dark Grey shale
33	46	Limstone	Notes:		
46	48	Green shale			
48	84	Tan shale			

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-yr) 2/12/2024 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451. This Water Well Record was completed on (mo-day-yr) 3/10/2024 under the business name of Holdeman Well Drilling Long St. Manhattan, KS