WATER WELL RECORD KSA 820-1201-1215 Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

			20-1201-121	J
17	\mathcal{W}	HE	SE	23

	County	Fraction		Section	number	Township number	Range number	NRL		
1. Location of well:	Riley	NE 1/4 NE 1/4 NE	1/4	2	2	т 9 s	r 7	(B/W		
2. Distance and direction from nearest town or city: 5 N oF				3. Owner of well: DUANC GILLAM						
Street address of well location if in city: MANJATAN				R.R. or street: City, state, zip code: MANATAN						
4. Locate with "X" in section below: Sketch map:						6. Bore hole dio. E in. Completion date				
N						Well depth 265 ft. 3-26-77				
House						7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary				
, , , , , , , , , , , , , , , , , , ,	1					8. Use: Domestic Public supply Industry				
. N 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ix E	!	weir		'eii	Irrigation Air conditioning Stock Lawn Oil field water Other				
SW SE Septic 300 X						9. Casing: Material	Height: Above or	below		
<u> </u>	<u> </u>		Threaded Welded Surface 24 in. RMP PVC 91 Weight 25 lbs./ft.							
S 1 Mi						Dia. Sin. to 265ft. depth Wall Thickness: inches or				
5. Type and color of	material			From	То	Dia in. to ft. dep 10. Screen: Manufacturer's		172K		
	1			٥	7	PUMPCO				
	4	m35 TONY	,		'	Type <u>マンと</u> 何 /gauze <u>: ら に</u>	Dia <u>3</u> Length <i>100</i>			
cimestoire, Shale, gray, Red, Soft Yellowshale				17	178	Set between 165 ft. and 265 ft.				
Limestone, Brooken, SOFT, Shaley			178	185	Grovel pack? Size range of material /41/8					
Shale, Bik. Red, gray shale				185	235	11. Static woter level:	rface Date <u>3 - z</u>	o./day/yr. 6-77		
Limes Towe, yellow, SUFT, BROKOW				235	250	12. Pumping level below lond surfaces:				
Shale, Lime, groy				250	265	ft. after hrs. pumping g.p.m g.p.m g.p.m.				
	, 176, 786					Estimated maximum yield — 13. Water sample submitted:		I.QQyI pm		
						Yes No	Date			
						14. Well head completion: C 4 P Pitless adapter				
				ļ		15. Well grouted?				
						With: Neat cement Bentonite Concrete Depth: From ft. to ft.				
						16. Nearest source of possible ft. 300 Direction		N		
. 4,-						ft. 300 Direction Well disinfected upon compl				
			<u></u>			17. Pump:	Not installed			
						Manufacturer's name Model number	HP V	olts		
						Length of drop pipe	ft. capacity			
						Type: Submersible	Turbi	ne la)		
	(1) = = ================================	heat if mandad)		1		Jet Centrifugal	Recip	procating 5		
18. Elevation:	(Use a second s	neer () Heeded/		1	I	20. Water well contractor's		─ ── °		
						This well was drilled under my jurisdiction and this report				
Topography: 0 WNER WILL INSTAL SLAB						is true to the best of my knowledge and belief. STRACE DRAG CO Tree 182 Business name License No.				
					Business name Address RTI HOITON, KS.					
Upland					Signed Authorized representative Date 3-28-7					
Valley		· · · · · · · · · · · · · · · · · · ·				Authorized rej	,, esemulive	⊁ /i }		