

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Riley	Fraction NW 1/4 NW 1/4 NW 1/4	Section number 23	Township number T 9 S R 7 E	Range number 7 E
2. Distance and direction from nearest town or city: 4 N OF MANHATTAN			Owner of well: ROBERT GOTK		
Street address of well location if in city: MANHATTAN			City, state, zip code: RR 4 MANHATTAN		
4. Locate with "X" in section below: N W E S 1 Mile			Sketch map: 		
5. Type and color of material			From	To	6. Bore hole dia. 8 in. Completion date 5-22-78 Well depth 220 ft.
TOP SOIL			0	3	7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary
Shale, yellow, grey			3	25	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
Limestone, shaley grey			25	29	9. Casing: Material PVC Height: above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 2 1/2 in. RMP <input type="checkbox"/> PVC 9L Weight 258 lbs./ft. Dia. 5 in. to 220 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 279
shale, grey, yellow			39	98	10. Screen: Manufacturer's name Pumpco MPI Type PVC Dia. 5" <input checked="" type="checkbox"/> 60# gauze .020 Length 90' Set between 160 ft. and 200' ft. ft. and <input type="checkbox"/> ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material .030x1000
shaley Lime, grey, brown			98	140	11. Static water level: <input type="checkbox"/> mo./day/yr. 185 ft. below land surface Date 5-22-78
shale, grey, blk.			140	183	12. Pumping level below land surfaces: ____ ft. after ____ hrs. pumping ____ g.p.m. ____ ft. after ____ hrs. pumping ____ g.p.m. Estimated maximum yield 15 g.p.m.
Limestone, yellow, broken, loose			183	185	13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date _____
shale, grey			185	220	14. Well head completion: cap <input type="checkbox"/> Pitless adapter 2 1/2 inches above grade
(Use a second sheet if needed)					15. Well grouted? <input checked="" type="checkbox"/> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 5 ft. to 15 ft.
18. Elevation:	19. Remarks: OWNER TO INSTAL SLAB		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Strader Dalg Catine 192 Business name License No. Address RT 1 Holton, KS Signed Dale Ashin Date 5-24-78 Authorized representative		

T-9-70m-23-NW 1/4