		R WELL RECORD	Form WV	VC-5	KSA 82a-	-1212				3	4	
1 LOCATION OF WATER WELL: Fraction		CT.T			Number	Town	ship Nu	mber	Range Number			
County: Riley	SE¼		SW 1/4		4	<u> </u>	9	S	R	7	(E)W	
Distance and direction from nearest tow			ated within c	ity?								
532 Lakeside Bivd.	. Manhattan.	Kansas										
2 WATER WELL OWNER: KDHE		-10										
	Field, Bldg	,				Boa	urd of Ag	riculture, D	ivision of	Water	Resource	
	Kansas 666						lication					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF C	OMPLETED WELL.	25	ft	. ELEVAT	TION:	· · · · · · ·		. 			
N		water Encountered										
7 ! ! !		WATER LEVEL										
NW Î NE	Pump	test data: Well w	ater was		ft. aft	ter		hours pun	nping		gpm	
	Est. Yield	gpm: Well wa	ater was		ft. aft	ter		hours pun	nping		gpm	
* W 1 1 E	Bore Hole Diame	ter8in.	to	6	ft., a	ınd		in.	to		ft.	
ž "!!!!	WELL WATER T	O BE USED AS:	5 Public v	water sup	oply 8	8 Air condi	itioning	11 li	njection v	veil		
	1 Domestic	3 Feedlot	6 Oil field	water s	upply !	9 Dewater	ing	12 (Other (Spe	ecify be	iow)	
1 - 7 - 1 - 1	2 Irrigation	4 Industrial	7 Lawn a	nd garde	n only (1	Monitori	ng well .	,				
	Was a chemical/b	acteriological sampl	e submitted t	to Depart	ment? Ye	sl	voХ	; If yes,	mo/day/yı	r sample	was sub	
<u> </u>	mitted				Wate	er Well Dis	infected	? Yes		vc X		
5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Cc	oncrete til	e	CASIN	NG JOIN	TS: Glued	0	Clamped	1	
1 Steel 3 RMP (SR)	6 Asbestos-Cemer	nt 9 Ot	her (spec	cify below)		Weide	d			
(2)PVC 4 ABS		7 Fiberglass						Thread	ded	X.		
Blank casing diameter	n. to 7 a.	ft., Dia	in	. to		ft., Dia		ir	n. to		ft.	
Casing height above land surface	36	in., weight	<u></u>		lbs./ft	t. Wall thick	kness or	gauge No	sc	n. 40		
TYPE OF SCREEN OR PERFORATION	MATERIAL:		(7	PVC		,	0 Asbes	stos-cemer	nt			
1 Steel 3 Stainless	steel	5 Fiberglass	8	RMP (S	R)	1	1 Other	(specify) .		. .		
2 Brass 4 Galvanize	d st eel	6 Concrete tile	9	ABS		•	12 None	used (ope	n hole)			
SCREEN OR PERFORATION OFENING	S ARE:	5 Gau	uzed wrappe	d		8 Saw cu	ıt		11 None	(open	hole)	
1 Continuous slot (3 Mill	slot	6 Wir	e wrapped			9 Drilled	holes				·	
2 Louvered shutter 4 Key	y punched		ch cut			10 Other (specify)					
SCREEN-PERFORATED INTERVALS:	From 7.	ft. to	25.		.ft., From			ft. to				
	From	ft. to		. <i></i>	.ft., From	1		ft. to		 .	ft.	
GRAVEL PACK INTERVALS:	From 5	ft. to	26.	. 	.ft., From	1		ft. to	<i></i>		ft.	
	From	ft. to			ft., From			ft. to			ft.	
6 GROUT MATERIAL: 1 Neat ce	ment (2	Cement grout		entonite	4 0	Other			·			
Grout Intervals: From 0fr	t. to 2	ft., From	2	ft. to	5	ft., Fr	om		. ft. to .		ft.	
What is the nearest source of possible of	ontamination:			. 1	0 Livesto	ock pens		14 Aba	andoned	water w	eli	
1 Septic tank 4 Lateral lines		7 Pit privy		(1	(11) Fuel storage			15 Oil well/Gas well				
2 Sewer lines 5 Cess pooi		8 Sewage lagoon		7	12 Fertilizer storage			16 Other (specify below)				
3 Watertight sewer lines 6 Seepage pit		9 Feedyard		1	13 insecticide storage							
Direction from well? Southeast				. 1	How many	y feet?	550					
FROM TO	LITHOLOGIC L	.OG	FROM	/ T	O		PLU	GGING IN	TERVALS	3		
0 14.5 Clay - brow												
14.5 15 Limestone -												
15 19.5 Limestone w												
19.5 21 Limestone -	- cherty											
21 22.5 Shale - yel	low tan											
22.5 23 Limestone -	- tan											
23 26 Limestone -	- gray											
									•			
						Mwi	10 - :	flushmo	ount			
			٠.									
CONTRACTOR'S OR LANDOWNER'S	S CERTIFICATIO	N: This water well	was (1) cons	structed	(2) recons	structed o	r (3) olu	aged unde	r my juris	diction	and was	
completed on (mo/day/year)	09–1	4-94				is true to						
Water Well Contractor's License No		This Water	Well Record	was con	npleted on	(mo/day/	/r) .		-06-94			
under the business name of		Core Services,			y (signatu		21.	G P	es :			
INSTRUCTIONS: Use typewriter or ball point pe							swers. Sen	d top three co	poies to Kan	sas Deca	rtmen#	
of Health and Environment, Bureau of Water, To												