USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215 Kansas Department of Health and Environment-Division of Environment (Water well Contractors)

							Topeka, K	ansas 66620		
1. Location of well:	County Fraction			Section number		Township number Range number				
i. Location of well:	POTAWATOMIE	NE 1/4 NE 1/4 SU	V 1/4		છ	т 9		8	<b>E</b> W	
2. Distance and direction from nearest town or city: 4.5 N of 3. Owner					r street: 1010 Westloop PL					
Street address of well location if in city: ManhaTTAN  R.R. or street: // City state via code: //						Westloop	o 1 <sup>r</sup> L	11-		
4. Locate with "X" in section below: Sketch map:					ode: ///	4nha7Tan, K 6. Bore hole dia. 12	ANS.	nletion date	02	
N					Well depth 250			3-2-79	7	
	No Co	INTAMINATION IN	/ Seve	7 1A4	1005474					
NW	NE Feet		1			Hollow rod J	etted	Bored Rev	verse rotary	
Free Well						8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock				
···						Lawn				
SW SE WATER Tower Oromage						9. Casing: Material QUC Height: (boy) or below				
. Lil		Threaded Welded  Surface in.								
S 1 M		•	~			Dia 5 in. to 250f				
5. Type and color of				From	То	Dia in. to f				
				<del> </del>		10. Screen: Manufactu				
Clay, bro	אנטופ			0	3	Type TVC	Dic	. 6		
				3		flod gauze . O b O	Len	gth <b>&amp;P</b> C		
Shale yellow, Red					53		_ft. and _		ft.	
Limestone, yellow				53	74	Gravel pack? S		f material 🖊	x//B	
shale, yellow, red				74	125	11. Static water level:			o./day/yr.	
•						12. Rumping level halo			-1-	
Shaley Lime, grey				125	165	12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m.				
Shale grey black				165	196	ft. after hrs. pumping g.p.m. Estimated maximum yield G.p.m.				
· ·				Int	265	Estimated maximum yie  13. Water sample submi		m	g.p.m.	
LimesTane, yellow water bearing					265	Yes No Date				
Shaley Linestone, grey					237	14. Well head completion:  — Pitless adapter 2 4 Inches above grade				
•				2.37	240	Pitless adapter  15. Well grouted?		Inches abov	e grade	
Shale, gray				J		With: Neat cement Bentonite Concrete			Concrete	
Shale, groy				240	250	Depth: From				
						16. Nearest source of p			ע	
						Well disinfected upon			No	
				1		17. Pump:		Not installe	d	
					<del> </del>	Manufacturer's name _ Model number		)\	/olts	
						Length of drop pipe —			g.p.m.	
						Type:		T.,L.	ina	
				-		Submersible Jet		Turb Reci	procating	
	(Use a second	d sheet if needed)				Centrifugal		Othe		
18. Elevation: 19. Remarks:						20. Water well contractor's certification: This well was drilled under my jurisdiction and this report				
	646 3146 W.	11 be CONST				This well was drilled u			nis report	
Topography:	DA D	or comat.				STRAGER DE		Inc	182	
Hill Slope						Business name	Ho/7	Tan, K	icense No.	
Slope Upland						Signed Oale	a	Com	te 3579	
Valley						Authoriz	ed represen	tative	,,	